

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 4 9
光源	LLD3000CU1 ×1 795.0 lm
管理番号	K0179071 (0) DR 1
B Z 分類	B Z 3

器具効率		84 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	55	46	41	37	54	46	41	37	52	45	40	37	51	44	40	37	35
			0.63	0.8	63	55	50	46	62	55	50	46	60	54	49	46	58	53	49	45	44
			0.56	1.0	68	61	56	52	67	60	56	52	65	59	55	52	63	58	54	51	50
				1.25	73	66	61	58	71	66	61	58	69	64	60	57	67	63	60	57	55
下方投影面積		c m ²		1.5	75	70	65	62	74	69	65	61	72	68	64	61	70	66	63	60	59
			等価発光面積	c m ²	2.0	79	75	71	68	78	74	70	67	76	72	69	66	74	71	68	66
取付 高さ	器具間隔最大限			2.5	82	78	74	71	80	77	74	71	78	75	72	70	76	74	71	69	67
	横方向 (A) 縦方向 (B)			3.0	83	80	77	74	82	79	76	74	80	77	75	73	78	76	74	72	70
H m	1.40 H m 1.40 H m			4.0	85	82	80	78	84	82	79	77	82	80	78	76	80	78	77	75	73
				5.0	86	84	82	80	85	83	81	80	83	81	80	78	81	80	78	77	75
				7.0	88	86	85	83	87	85	84	82	85	83	82	81	83	82	81	80	77
				10.0	89	88	86	85	88	87	86	85	86	85	84	83	84	83	82	82	79

