

屋内照明器具特性

品番 (品名)	LGS9504	
光源	LLD2000LCS1 ×1	580.0 lm
管理番号	K0183279(0)DR1	
BZ分類	BZ5	

器具効率	95%	天井	80%				70%				50%				30%				0%		
	上方光束		16%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		79%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	5.2	4.1	3.4	2.9	5.0	4.0	3.3	2.9	4.7	3.8	3.2	2.8	4.3	3.6	3.1	2.7	2.4	
	中	0.63	0.8	6.1	5.1	4.3	3.8	5.9	4.9	4.2	3.8	5.5	4.6	4.1	3.6	5.1	4.4	3.9	3.5	3.1	
	否	0.56	1.0	6.7	5.7	5.0	4.5	6.5	5.6	4.9	4.4	6.0	5.2	4.7	4.2	5.6	4.9	4.4	4.1	3.7	
			1.25	7.2	6.3	5.7	5.1	7.0	6.2	5.5	5.0	6.5	5.8	5.3	4.8	6.0	5.4	5.0	4.6	4.2	
下方投影面積	c m ²		1.5	7.6	6.8	6.1	5.6	7.3	6.6	6.0	5.5	6.8	6.2	5.7	5.3	6.3	5.8	5.4	5.0	4.6	
	等価発光面積		c m ²	2.0	8.1	7.4	6.8	6.4	7.8	7.2	6.7	6.2	7.3	6.8	6.3	5.9	6.8	6.3	6.0	5.7	5.2
取付高さ	器具間隔最大限		2.5	8.4	7.8	7.3	6.9	8.1	7.6	7.1	6.7	7.6	7.1	6.7	6.4	7.1	6.7	6.4	6.1	5.5	
	横方向 (A)	縦方向 (B)	3.0	8.7	8.1	7.7	7.2	8.4	7.9	7.4	7.1	7.8	7.4	7.0	6.7	7.3	7.0	6.7	6.4	5.8	
H m	1.25 H m	1.25 H m	4.0	8.9	8.5	8.1	7.8	8.6	8.2	7.9	7.6	8.1	7.8	7.5	7.2	7.6	7.3	7.1	6.8	6.2	
			5.0	9.1	8.7	8.4	8.1	8.8	8.5	8.2	7.9	8.3	8.0	7.7	7.5	7.7	7.5	7.3	7.1	6.5	
			7.0	9.3	9.0	8.8	8.5	9.0	8.8	8.5	8.3	8.5	8.3	8.1	7.9	7.9	7.8	7.6	7.5	6.8	
			10.0	9.5	9.3	9.1	8.9	9.2	9.0	8.8	8.7	8.6	8.5	8.3	8.2	8.1	8.0	7.9	7.7	7.1	

