

# 屋内照明器具特性

|         |                                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|-----------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | LGS9504                           |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LLD40402CQ1 (KAKUSAN) ×1 860.0 1m |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0184332 (0) DR1                  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ4/3.5/BZ5                       |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |                  |      |      |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |    |    |
|--------|------------------|------------------|------|------|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|----|----|
| 器具効率   | 78%              | 天井               | 80%  |      |    |     | 70% |    |    |     | 50% |    |    |     | 30% |    |    |     | 0% |    |    |
|        | 上方光束             |                  | 12%  | 反射率  | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30 | 10 | 0% |
|        | 下方光束             |                  | 66%  |      | 床  | 10% |     |    |    | 10% |     |    |    | 10% |     |    |    | 10% |    |    |    |
| 室指数    | 照明率 (X0.01) ZCM  |                  |      |      |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |    |    |
| 保守率    | 良                | 0.67             | 0.6  | 45   | 36 | 30  | 26  | 43 | 35 | 30  | 26  | 40 | 33 | 29  | 25  | 38 | 32 | 28  | 25 | 22 |    |
|        | 中                | 0.63             | 0.8  | 52   | 44 | 38  | 34  | 50 | 43 | 37  | 34  | 47 | 41 | 36  | 32  | 44 | 38 | 35  | 31 | 29 |    |
|        | 否                | 0.56             | 1.0  | 57   | 49 | 44  | 40  | 55 | 48 | 43  | 39  | 51 | 45 | 41  | 38  | 48 | 43 | 39  | 36 | 33 |    |
|        | 下方投影面積           | c m <sup>2</sup> |      | 1.25 | 61 | 54  | 49  | 45 | 59 | 53  | 48  | 44 | 55 | 50  | 46  | 42 | 52 | 47  | 44 | 41 | 38 |
| 等価発光面積 | c m <sup>2</sup> |                  | 1.5  | 64   | 58 | 53  | 49  | 62 | 56 | 52  | 48  | 58 | 53 | 49  | 46  | 54 | 50 | 47  | 44 | 41 |    |
|        | c m <sup>2</sup> |                  | 2.0  | 68   | 63 | 58  | 55  | 66 | 61 | 57  | 53  | 62 | 58 | 54  | 51  | 58 | 54 | 52  | 49 | 45 |    |
| 取付高さ   | 器具間隔最大限          |                  | 2.5  | 70   | 66 | 62  | 58  | 68 | 64 | 60  | 57  | 64 | 60 | 57  | 55  | 60 | 57 | 55  | 52 | 48 |    |
|        | 横方向 (A)          | 縦方向 (B)          | 3.0  | 72   | 68 | 64  | 61  | 70 | 66 | 63  | 60  | 66 | 62 | 60  | 57  | 62 | 59 | 57  | 55 | 51 |    |
| H m    | 1.22 H m         | 1.22 H m         | 4.0  | 74   | 71 | 68  | 65  | 72 | 69 | 66  | 64  | 68 | 65 | 63  | 61  | 64 | 62 | 60  | 58 | 54 |    |
|        |                  |                  | 5.0  | 76   | 73 | 70  | 68  | 73 | 71 | 68  | 66  | 69 | 67 | 65  | 63  | 65 | 63 | 62  | 60 | 55 |    |
|        |                  |                  | 7.0  | 77   | 75 | 73  | 71  | 75 | 73 | 71  | 70  | 71 | 69 | 68  | 66  | 67 | 65 | 64  | 63 | 58 |    |
|        |                  |                  | 10.0 | 78   | 77 | 75  | 74  | 76 | 75 | 73  | 72  | 72 | 71 | 70  | 69  | 68 | 67 | 66  | 65 | 60 |    |

