

屋内照明器具特性

品番 (品名)	LGS9302	
光源	LLD2020LCB1 × 2	460.0 1m
管理番号	K0179483(0)DR1	
BZ分類	BZ1	

器具効率	96%	天井	80%				70%				50%				30%				0%	
	上方光束 1%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	95%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	80	74	70	68	79	74	70	68	78	73	70	68	77	73	70	67	66	
	中 0.63		0.8	86	80	77	74	85	80	76	74	83	79	76	74	82	78	75	73	72
	否 0.56		1.0	89	84	81	78	88	84	81	78	86	83	80	78	85	82	79	77	76
下方投影面積 等価発光面積	cm ²	1.25	92	88	84	82	91	87	84	82	89	86	83	81	87	85	82	81	79	
		1.5	94	90	87	85	93	89	87	84	91	88	86	84	89	87	85	83	81	
取付高さ	器具間隔最大限		2.5	98	95	93	91	96	94	92	90	94	92	91	89	93	91	90	88	86
	横方向 (A)	縦方向 (B)	3.0	99	96	94	93	97	95	94	92	95	94	92	91	93	92	91	90	88
Hm	0.41Hm	0.41Hm	4.0	100	98	96	95	99	97	96	94	97	95	94	93	95	93	92	92	89
			5.0	101	99	98	97	99	98	97	96	97	96	95	94	95	94	93	93	90
			7.0	101	100	99	98	100	99	98	97	98	97	96	96	96	95	95	94	92
			10.0	102	101	100	100	100	99	99	99	99	98	97	97	96	96	95	92	

