

屋内照明器具特性

品番 (品名)	LGS9302	
光源	LLD4000LCB1 ×2	845.0 lm
管理番号	K0179479(0)DR1	
BZ分類	BZ4/8.5/BZ5	

器具効率	76%	天井	80%				70%				50%				30%				0%							
	上方光束		9%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%					
	下方光束		67%	壁	10%				10%				10%				10%				0%					
室指数	照明率 (×0.01)																				ZCM					
保守率	良	0.67	0.6	4.4	3.5	3.0	2.6	4.2	3.4	2.9	2.6	4.0	3.3	2.8	2.5	3.8	3.2	2.8	2.4	2.3						
	中	0.63	0.8	5.1	4.3	3.8	3.4	5.0	4.2	3.7	3.4	4.7	4.1	3.6	3.3	4.4	3.9	3.5	3.2	3.0						
	否	0.56	1.0	5.6	4.9	4.4	4.0	5.5	4.8	4.3	3.9	5.1	4.6	4.1	3.8	4.9	4.4	4.0	3.7	3.5						
	下方投影面積	c m ²		1.25	6.1	5.4	4.9	4.5	5.9	5.3	4.8	4.4	5.5	5.0	4.6	4.3	5.2	4.8	4.5	4.2	3.9					
取付高さ	器具間隔最大限		H m	1.25 H m	1.25 H m	2.0	6.3	5.7	5.3	4.9	6.2	5.6	5.2	4.8	5.8	5.4	5.0	4.7	5.5	5.1	4.8	4.6	4.3	4.0	3.7	3.5
	横方向 (A)	縦方向 (B)																								
H m	1.25 H m		1.25 H m		2.5	7.0	6.5	6.2	5.9	6.8	6.4	6.0	5.8	6.4	6.1	5.8	5.6	6.1	5.8	5.6	5.4	5.0				
	1.25 H m		1.25 H m		3.0	7.1	6.7	6.4	6.1	6.9	6.6	6.3	6.0	6.6	6.3	6.0	5.8	6.2	6.0	5.8	5.6	5.3				
	1.25 H m		1.25 H m		4.0	7.3	7.0	6.8	6.5	7.1	6.9	6.6	6.4	6.8	6.6	6.3	6.2	6.4	6.3	6.1	5.9	5.5				
	1.25 H m		1.25 H m		5.0	7.5	7.2	7.0	6.8	7.3	7.0	6.8	6.6	6.9	6.7	6.5	6.4	6.6	6.4	6.3	6.1	5.7				
1.25 H m		1.25 H m		7.0	7.6	7.4	7.2	7.1	7.4	7.2	7.1	6.9	7.1	6.9	6.8	6.6	6.7	6.6	6.5	6.4	6.0					
1.25 H m		1.25 H m		10.0	7.7	7.6	7.4	7.3	7.5	7.4	7.3	7.2	7.2	7.1	7.0	6.9	6.8	6.7	6.7	6.6	6.2					

