

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 1 8
光源	LLD4000LCT1 ×1 845.0 l m
管理番号	K0190516 (0) DR 1
B Z 分類	B Z 3

器具効率		67 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
					床	10 %				10 %				10 %				10 %				0 %	
						室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	44	37	33	30	44	37	33	30	42	36	33	30	41	36	32	30	29		
			0.63	0.8	50	44	39	36	49	43	39	36	48	43	39	36	46	42	38	36	35		
			0.56	1.0	54	48	44	41	53	48	44	40	51	47	43	40	50	46	43	40	39		
			0.56	1.25	57	52	48	45	56	51	48	45	55	50	47	44	53	49	46	44	43		
下方投影面積		c m ²	1.5	60	55	51	48	59	54	51	48	57	53	50	47	55	52	49	47	46			
等価発光面積			c m ²	2.0	63	59	55	53	62	58	55	52	60	57	54	52	58	56	53	51	50		
				2.5	65	61	58	56	64	61	58	55	62	59	57	55	60	58	56	54	53		
取付 高さ	器具間隔最大限		3.0	66	63	60	58	65	62	60	58	63	61	59	57	62	60	58	56	55			
	横方向 (A)			縦方向 (B)		4.0	68	65	63	61	67	65	63	61	60	63	62	60	59	57			
H m	1.32 H m		1.32 H m		5.0		69	67	65	63	68	66	64	63	66	65	63	62	61	59			
			7.0	70			68	67	66	69	68	66	65	67	66	65	64	66	65	64	63	61	
				10.0			71	70	69	68	70	69	68	67	68	67	67	66	67	66	65	65	63

