

屋内照明器具特性	
品番 (品名)	LGC48200
光源	LED9999_70_4899 x1 4899.0 lm
管理番号	K0155362(0)D 1
BZ分類	BZ6/0.7/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 25%		下方光束 75%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.63	0.6	51	39	31	26	49	37	30	25	44	34	28	24	39	32	26	22	19
	中	0.6	0.6	60	49	41	35	57	47	39	34	52	43	37	32	47	39	34	30	25
	否	0.56	0.6	67	56	48	42	63	53	46	40	57	49	43	38	51	45	40	35	30
	0.56	0.6	73	62	55	49	69	60	53	47	62	55	49	44	56	50	45	41	35	
下方投影面積	c m <sup>2</sup>		1.25	73	62	55	49	69	60	53	47	62	55	49	44	56	50	45	41	35
	等価発光面積		c m <sup>2</sup>	1.5	77	67	60	54	73	64	58	52	66	59	54	49	60	54	49	46
取付高さ	器具間隔最大限		2.0	82	74	68	62	78	71	65	60	71	65	60	56	64	60	56	52	45
	横方向 (A)	縦方向 (B)	2.5	86	79	73	68	82	76	70	66	74	69	65	61	68	64	60	57	49
1.5m	1.95m	2.01m	3.0	88	82	77	72	84	79	74	70	77	72	69	65	70	66	63	60	53
2	2.57	2.65	4.0	92	87	82	78	88	83	79	76	80	77	73	70	73	70	68	65	57
2.5	3.21	3.3	5.0	94	90	86	82	90	86	83	79	82	79	76	74	75	73	70	68	60
3	3.82	3.92	7.0	96	93	90	87	92	89	87	84	85	82	80	78	77	76	74	72	63
			10.0	98	96	93	91	94	92	90	88	87	85	83	82	79	78	77	75	66

