

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 4 8
光源	L L D 5 0 2 0 L C C 1 × 1 1 0 8 5 . 0 l m
管理番号	K 0 1 9 0 4 2 7 (0) D R 1
B Z 分類	B Z 1

器具効率		8 1 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		8 1 %																					
保守率		良	0 . 6 7	0 . 6	6 8	6 4	6 1	5 9	6 8	6 4	6 1	5 9	6 7	6 3	6 0	5 9	6 6	6 3	6 0	5 8	5 8		
		中	0 . 6 3	0 . 8	7 3	6 9	6 7	6 4	7 3	6 9	6 6	6 4	7 2	6 8	6 6	6 4	7 1	6 8	6 6	6 4	6 3		
		否	0 . 5 6	1 . 0	7 6	7 3	7 0	6 8	7 6	7 2	7 0	6 8	7 4	7 1	6 9	6 8	7 3	7 1	6 9	6 7	6 6		
					1 . 2 5	7 9	7 6	7 3	7 1	7 8	7 5	7 3	7 1	7 7	7 4	7 2	7 1	7 5	7 3	7 2	7 0	6 9	
下方投影面積		c m ²	1 . 5	8 0	7 7	7 5	7 4	7 9	7 7	7 5	7 3	7 8	7 6	7 4	7 3	7 7	7 5	7 4	7 2	7 1			
			2 . 0	8 2	8 0	7 8	7 7	8 1	7 9	7 8	7 6	8 0	7 8	7 7	7 6	7 8	7 7	7 6	7 5	7 4			
取付 高さ	器具間隔最大限		2 . 5	8 3	8 1	8 0	7 9	8 2	8 1	7 9	7 8	8 1	8 0	7 8	7 7	7 9	7 8	7 7	7 7	7 5			
	横方向 (A)	縦方向 (B)	3 . 0	8 4	8 2	8 1	8 0	8 3	8 2	8 1	8 0	8 2	8 0	7 9	7 9	8 0	7 9	7 8	7 8	7 6			
H m	0 . 4 1 H m	0 . 4 1 H m	4 . 0	8 5	8 4	8 3	8 2	8 4	8 3	8 2	8 1	8 2	8 2	8 1	8 0	8 1	8 0	8 0	7 9	7 7			
			5 . 0	8 6	8 5	8 4	8 3	8 5	8 4	8 3	8 2	8 3	8 2	8 2	8 1	8 1	8 1	8 0	8 0	7 8			
			7 . 0	8 6	8 6	8 5	8 4	8 5	8 5	8 4	8 4	8 4	8 3	8 3	8 2	8 2	8 2	8 1	8 1	7 9			
			1 0 . 0	8 7	8 6	8 6	8 5	8 6	8 5	8 5	8 5	8 4	8 4	8 3	8 3	8 2	8 2	8 2	8 2	8 0			

