

屋内照明器具特性

品番 (品名)	NNY20247K														
光源	LED5000_70_1555 x1 1555.0 lm														
管理番号	K0167903(0)DR1														
BZ分類	BZ9														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束 下方光束	50% 50%	室指数	照明率 (X0.01) ZCM																	
保守率	良 中 否 0.63 0.6 0.56	0.6	44	32	24	18	40	29	22	17	33	24	18	14	26	19	15	11	6	
		0.8	52	40	32	25	48	37	29	23	39	30	24	20	31	25	20	16	9	
		1.0	58	46	38	31	53	42	35	29	44	35	29	24	35	28	23	19	11	
		1.25	64	52	44	37	58	48	41	35	48	40	34	29	38	32	27	24	14	
下方投影面積 等価発光面積	c m ² c m ²	1.5	68	57	49	42	62	53	45	39	51	44	38	33	41	35	31	27	17	
		2.0	73	64	56	50	67	59	52	46	56	49	44	39	45	40	36	32	21	
取付 高さ	器具間隔最大限		2.5	77	69	62	56	71	63	57	52	59	53	48	44	48	43	39	36	24
	横方向 (A) H m	縦方向 (B) H m	3.0	80	72	66	60	73	67	61	56	61	56	51	47	50	46	42	39	26
			4.0	83	77	72	67	77	71	66	62	64	60	56	52	53	49	46	43	29
			5.0	86	80	75	71	79	74	70	66	66	63	59	56	55	52	49	47	32
			7.0	88	84	80	77	82	78	74	71	69	66	63	61	57	55	53	51	35
			10.0	91	87	84	81	84	81	78	76	71	69	67	65	59	58	56	54	38

