

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | LGS9301                      |
| 光源       | LLD4000LCB1 x2      845.0 lm |
| 管理番号     | K0179469(0)DR1               |
| BZ分類     | BZ4/1.1/BZ3/3.5/BZ4          |

|        |         |         |              |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |     |    |
|--------|---------|---------|--------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率   | 54%     | 天井      | 80%          |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0%  |    |
|        |         | 壁       | 70           | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 0%      | 床       | 10%          |    |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 54%     | 室指数     | 照明率 ( X0.01) |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    | ZCM |    |
| 保守率    | 良       | 0.67    | 0.6          | 33 | 26 | 22 | 20  | 32 | 26 | 22 | 20  | 31 | 25 | 22 | 19  | 30 | 25 | 22 | 19  | 18 |
|        | 中       | 0.63    | 0.8          | 38 | 33 | 29 | 26  | 38 | 32 | 28 | 26  | 36 | 31 | 28 | 26  | 35 | 31 | 28 | 25  | 24 |
|        | 否       | 0.56    | 1.0          | 42 | 37 | 33 | 30  | 41 | 36 | 33 | 30  | 40 | 35 | 32 | 30  | 38 | 35 | 32 | 30  | 29 |
|        |         |         | 1.25         | 45 | 41 | 37 | 34  | 44 | 40 | 37 | 34  | 43 | 39 | 36 | 34  | 41 | 38 | 36 | 34  | 33 |
| 下方投影面積 |         |         | 1.5          | 47 | 43 | 40 | 37  | 46 | 43 | 40 | 37  | 45 | 42 | 39 | 37  | 43 | 41 | 38 | 36  | 35 |
|        |         |         | 2.0          | 50 | 47 | 44 | 42  | 49 | 46 | 44 | 41  | 48 | 45 | 43 | 41  | 46 | 44 | 42 | 40  | 39 |
| 取付高さ   | 器具間隔最大限 |         | 2.5          | 52 | 49 | 46 | 44  | 51 | 48 | 46 | 44  | 49 | 47 | 45 | 44  | 48 | 46 | 44 | 43  | 42 |
|        | 横方向 (A) | 縦方向 (B) | 3.0          | 53 | 50 | 48 | 46  | 52 | 50 | 48 | 46  | 51 | 49 | 47 | 45  | 49 | 48 | 46 | 45  | 44 |
| Hm     | 1.29Hm  | 1.29Hm  | 4.0          | 54 | 52 | 51 | 49  | 54 | 52 | 50 | 49  | 52 | 51 | 49 | 48  | 51 | 50 | 48 | 47  | 46 |
|        |         |         | 5.0          | 55 | 54 | 52 | 51  | 55 | 53 | 52 | 50  | 53 | 52 | 51 | 50  | 52 | 51 | 50 | 49  | 47 |
|        |         |         | 7.0          | 56 | 55 | 54 | 53  | 56 | 54 | 53 | 52  | 54 | 53 | 52 | 52  | 53 | 52 | 51 | 51  | 49 |
|        |         |         | 10.0         | 57 | 56 | 55 | 55  | 56 | 56 | 55 | 54  | 55 | 54 | 54 | 53  | 54 | 53 | 53 | 52  | 50 |

