

# 屋内照明器具特性

品番 (品名)	LGC41162														
光源	LED6200_70_4899 x1 4899.0 lm														
管理番号	K0147596(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	8%	室指数																			
下方光束	92%	照明率 (X0.01)																			
保守率	良 中 否	0.63 0.6 0.56	0.6	5.4	4.2	3.4	2.9	5.3	4.1	3.4	2.8	5.0	3.9	3.3	2.8	4.7	3.8	3.2	2.7	2.5	
			0.8	6.4	5.2	4.4	3.8	6.2	5.1	4.4	3.8	5.8	4.9	4.2	3.7	5.5	4.7	4.1	3.6	3.4	
下方投影面積	c m <sup>2</sup>	1.25	7.6	6.6	5.9	5.3	7.4	6.5	5.8	5.2	7.0	6.2	5.6	5.1	6.6	5.9	5.4	4.9	4.6		
			1.5	8.0	7.1	6.4	5.8	7.8	7.0	6.3	5.7	7.4	6.7	6.1	5.6	7.0	6.4	5.9	5.4	5.1	
等価発光面積	c m <sup>2</sup>	2.0	8.6	7.8	7.2	6.6	8.4	7.6	7.0	6.5	7.9	7.3	6.8	6.3	7.5	7.0	6.6	6.2	5.8		
			2.5	9.0	8.3	7.7	7.2	8.7	8.1	7.5	7.1	8.3	7.7	7.3	6.9	7.9	7.4	7.0	6.7	6.3	
取付高さ	器具間隔最大限		3.0	9.2	8.6	8.1	7.6	9.0	8.4	7.9	7.5	8.5	8.1	7.6	7.3	8.1	7.7	7.4	7.1	6.6	
	横方向 (A)	縦方向 (B)																			
H m	1.27 H m	1.27 H m	4.0	9.5	9.0	8.6	8.2	9.3	8.9	8.4	8.1	8.9	8.5	8.1	7.8	8.4	8.1	7.8	7.6	7.1	
			5.0	9.7	9.3	8.9	8.6	9.5	9.1	8.8	8.5	9.1	8.8	8.5	8.2	8.7	8.4	8.2	7.9	7.5	
			7.0	10.0	9.7	9.4	9.1	9.8	9.5	9.2	8.9	9.3	9.1	8.9	8.6	8.9	8.7	8.5	8.3	7.9	
			10.0	10.2	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.5	9.3	9.2	9.0	9.1	9.0	8.8	8.7	8.2	

