

屋内照明器具特性

品番 (品名)	LGD1321L	
光源	LED2700_70_90 x1	90.0 lm
管理番号	K0170888(0)DR1	
BZ分類	BZ1	

器具効率	98%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	98%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	96	93	91	90	95	92	91	89	94	92	90	89	94	92	90	89	89	
	中 0.63		0.8	98	95	94	92	98	95	93	92	97	95	93	92	96	94	93	92	91
	否 0.56		1.0	100	97	95	94	99	97	95	94	98	96	95	94	97	95	94	93	92
下方投影面積 等価発光面積	cm ²	1.25	101	99	97	96	100	98	97	96	99	97	96	95	98	96	95	94	93	
		1.5	102	100	98	97	101	99	98	97	100	98	97	96	98	97	96	95	94	
		2.0	103	101	100	99	102	101	99	98	100	99	98	97	99	98	97	97	95	
取付高さ	器具間隔最大限		2.5	104	102	101	100	103	101	100	99	101	100	99	98	99	99	98	97	96
	横方向 (A)	縦方向 (B)	3.0	104	103	102	101	103	102	101	100	101	100	100	99	100	99	98	98	96
Hm	0.23Hm	0.23Hm	4.0	105	104	103	102	104	103	102	101	102	101	100	100	99	99	99	99	96
			5.0	105	104	103	103	104	103	103	102	102	101	101	100	100	100	99	99	97
			7.0	105	105	104	104	104	104	103	103	102	102	101	101	100	100	100	99	97
			10.0	106	105	105	104	105	104	104	103	103	102	102	101	101	100	100	100	97

