

# 屋内照明器具特性

|         |                             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|-----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XAD3 2 0 1 V                |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED3500_70_710 x1 710.0 l m |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0165460 ( 0 ) DB 1         |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| B Z 分類  | BZ4 / 0.7 / BZ3             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |          |               |      |     |     |      |      |     |     |      |      |     |     |      |      |    |    |     |     |
|--------|------------------|----------|---------------|------|-----|-----|------|------|-----|-----|------|------|-----|-----|------|------|----|----|-----|-----|
| 器具効率   | 100 %            | 天井       | 80 %          |      |     |     | 70 % |      |     |     | 50 % |      |     |     | 30 % |      |    |    | 0 % |     |
|        |                  |          | 壁             | 70   | 50  | 30  | 10   | 70   | 50  | 30  | 10   | 70   | 50  | 30  | 10   | 70   | 50 | 30 | 10  | 0 % |
| 上方光束   | 0 %              | 反射率      | 10 %          |      |     |     | 10 % |      |     |     | 10 % |      |     |     | 10 % |      |    |    | 0 % |     |
| 下方光束   | 100 %            |          | 床             | 10 % |     |     |      | 10 % |     |     |      | 10 % |     |     |      | 10 % |    |    |     | 0 % |
|        |                  | 室指数      | 照明率 ( X0.01 ) |      |     |     |      |      |     |     |      |      |     |     |      |      |    |    | ZCM |     |
| 保守率    | 良<br>中<br>否      | 0.67     | 0.6           | 61   | 50  | 43  | 38   | 60   | 50  | 43  | 38   | 58   | 49  | 42  | 38   | 56   | 48 | 42 | 38  | 36  |
|        |                  | 0.63     | 0.8           | 72   | 62  | 55  | 50   | 71   | 61  | 55  | 50   | 68   | 60  | 54  | 50   | 66   | 59 | 53 | 49  | 47  |
|        |                  | 0.56     | 1.0           | 79   | 70  | 63  | 58   | 77   | 69  | 63  | 58   | 75   | 68  | 62  | 58   | 73   | 66 | 61 | 57  | 55  |
|        |                  |          | 1.25          | 85   | 77  | 71  | 66   | 83   | 76  | 70  | 66   | 81   | 74  | 69  | 65   | 78   | 73 | 68 | 65  | 63  |
| 下方投影面積 | c m <sup>2</sup> | 1.5      | 89            | 81   | 76  | 71  | 87   | 81   | 75  | 71  | 84   | 79   | 74  | 71  | 82   | 77   | 73 | 70 | 68  |     |
|        |                  | 2.0      | 94            | 88   | 83  | 79  | 92   | 87   | 82  | 79  | 90   | 85   | 81  | 78  | 87   | 83   | 80 | 77 | 75  |     |
| 取付高さ   | 器具間隔最大限          |          | 2.5           | 97   | 92  | 88  | 84   | 95   | 91  | 87  | 84   | 93   | 89  | 86  | 83   | 90   | 87 | 84 | 82  | 79  |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0           | 99   | 94  | 91  | 88   | 97   | 93  | 90  | 87   | 95   | 91  | 89  | 86   | 92   | 90 | 87 | 85  | 83  |
| H m    | 1.24 H m         | 1.24 H m | 4.0           | 101  | 98  | 95  | 92   | 100  | 97  | 94  | 92   | 97   | 95  | 92  | 90   | 95   | 93 | 91 | 89  | 87  |
|        |                  |          | 5.0           | 103  | 100 | 98  | 95   | 101  | 99  | 97  | 95   | 99   | 97  | 95  | 93   | 96   | 95 | 93 | 92  | 89  |
|        |                  |          | 7.0           | 104  | 102 | 100 | 99   | 103  | 101 | 100 | 98   | 101  | 99  | 98  | 96   | 98   | 97 | 96 | 95  | 92  |
|        |                  |          | 10.0          | 105  | 104 | 103 | 102  | 104  | 103 | 102 | 101  | 102  | 101 | 100 | 99   | 100  | 99 | 98 | 97  | 94  |

