

# 屋内照明器具特性

品番 (品名)	XAS3002V				
光源	LED3500_70_600 x1		600.0 l m		
管理番号	K0170907(0)DB1				
BZ分類	BZ4/1.1/BZ3/3.5/BZ4				

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.67	0.6	60	49	41	36	59	48	41	36	57	47	41	36	55	46	40	36	34
	中	0.63	0.8	71	60	53	48	69	59	53	48	67	58	52	47	64	57	51	47	45
	否	0.56	1.0	77	68	61	56	76	67	60	56	73	65	60	55	71	64	59	55	53
			1.25	83	75	68	63	82	74	68	63	79	72	67	63	76	71	66	62	60
下方投影面積	c m <sup>2</sup>		1.5	87	79	74	69	86	79	73	68	83	77	72	68	80	75	71	67	65
等価発光面積	c m <sup>2</sup>		2.0	92	86	81	77	91	85	80	76	88	83	79	75	85	81	78	75	72
取付高さ	器具間隔最大限		2.5	95	90	86	82	94	89	85	81	91	87	83	80	88	85	82	79	77
	横方向 (A)	縦方向 (B)	3.0	97	93	89	86	96	92	88	85	93	90	87	84	91	88	85	83	80
H m	1.29 H m	1.29 H m	4.0	100	97	93	90	99	95	92	90	96	93	91	88	94	91	89	87	85
			5.0	102	99	96	94	100	98	95	93	98	95	93	91	95	93	92	90	87
			7.0	104	101	99	97	102	100	98	97	100	98	96	95	97	96	95	93	90
			10.0	105	103	102	100	104	102	101	100	101	100	99	98	99	98	97	96	93

