

|          |                            |
|----------|----------------------------|
| 屋内照明器具特性 |                            |
| 品番 (品名)  | XAS3001N                   |
| 光源       | LED5000_70_660 x1 660.0 lm |
| 管理番号     | K0166825(0)D 1             |
| BZ分類     | BZ5                        |

|        |         |                 |              |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    |     |    |
|--------|---------|-----------------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|----|----|----|-----|----|
| 器具効率   | 100%    | 天井              | 80%          |     |     |     | 70% |     |     |     | 50% |     |    |    | 30% |    |    |    | 0%  |    |
|        |         | 壁               | 70           | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 0%      | 床               | 10%          |     |     |     | 10% |     |     |     | 10% |     |    |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 100%    | 室指数             | 照明率 ( X0.01) |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    | ZCM |    |
| 保守率    | 良       | 0.67            | 0.6          | 57  | 45  | 37  | 32  | 56  | 44  | 37  | 32  | 54  | 43 | 37 | 32  | 51 | 42 | 36 | 32  | 30 |
|        | 中       | 0.63            | 0.8          | 67  | 56  | 48  | 42  | 66  | 55  | 48  | 42  | 63  | 54 | 47 | 42  | 61 | 52 | 46 | 42  | 40 |
|        | 否       | 0.56            | 1.0          | 74  | 63  | 56  | 50  | 72  | 62  | 55  | 50  | 69  | 61 | 54 | 49  | 67 | 59 | 54 | 49  | 47 |
|        |         |                 | 1.25         | 80  | 70  | 63  | 58  | 78  | 69  | 63  | 57  | 75  | 68 | 62 | 57  | 73 | 66 | 61 | 56  | 54 |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5          | 84  | 75  | 69  | 63  | 82  | 74  | 68  | 63  | 79  | 72 | 67 | 62  | 77 | 71 | 66 | 62  | 59 |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0          | 90  | 82  | 77  | 72  | 88  | 81  | 76  | 71  | 85  | 79 | 75 | 70  | 82 | 77 | 73 | 70  | 67 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5          | 93  | 87  | 82  | 77  | 92  | 86  | 81  | 77  | 89  | 84 | 80 | 76  | 86 | 82 | 78 | 75  | 72 |
|        | 横方向 (A) | 縦方向 (B)         | 3.0          | 96  | 90  | 86  | 82  | 94  | 89  | 85  | 81  | 91  | 87 | 83 | 80  | 88 | 85 | 82 | 79  | 76 |
| Hm     | 1.26Hm  | 1.26Hm          | 4.0          | 99  | 95  | 91  | 87  | 97  | 93  | 90  | 87  | 94  | 91 | 88 | 85  | 92 | 89 | 86 | 84  | 82 |
|        |         |                 | 5.0          | 101 | 97  | 94  | 91  | 99  | 96  | 93  | 90  | 96  | 94 | 91 | 89  | 94 | 92 | 89 | 88  | 85 |
|        |         |                 | 7.0          | 103 | 100 | 98  | 96  | 101 | 99  | 97  | 95  | 99  | 97 | 95 | 93  | 96 | 95 | 93 | 92  | 89 |
|        |         |                 | 10.0         | 104 | 103 | 101 | 99  | 103 | 101 | 100 | 98  | 101 | 99 | 98 | 96  | 98 | 97 | 96 | 95  | 92 |

