

# 屋内照明器具特性

品番 (品名)	XAS3500L				
光源	LED2700_70_700 ×1		700.0 lm		
管理番号	K0166825(0)D 1				
BZ分類	BZ5				

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%																			
下方光束	100%																			
		室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	5.7	4.5	3.7	3.2	5.6	4.4	3.7	3.2	5.4	4.3	3.7	3.2	5.1	4.2	3.6	3.2	3.0
	中	0.63	0.8	6.7	5.6	4.8	4.2	6.6	5.5	4.8	4.2	6.3	5.4	4.7	4.2	6.1	5.2	4.6	4.2	4.0
	否	0.56	1.0	7.4	6.3	5.6	5.0	7.2	6.2	5.5	5.0	6.9	6.1	5.4	4.9	6.7	5.9	5.4	4.9	4.7
			1.25	8.0	7.0	6.3	5.8	7.8	6.9	6.3	5.7	7.5	6.8	6.2	5.7	7.3	6.6	6.1	5.6	5.4
下方投影面積		cm <sup>2</sup>	1.5	8.4	7.5	6.9	6.3	8.2	7.4	6.8	6.3	7.9	7.2	6.7	6.2	7.7	7.1	6.6	6.2	5.9
等価発光面積		cm <sup>2</sup>	2.0	9.0	8.2	7.7	7.2	8.8	8.1	7.6	7.1	8.5	7.9	7.5	7.0	8.2	7.7	7.3	7.0	6.7
取付高さ	器具間隔最大限		2.5	9.3	8.7	8.2	7.7	9.2	8.6	8.1	7.7	8.9	8.4	8.0	7.6	8.6	8.2	7.8	7.5	7.2
	横方向 (A)	縦方向 (B)	3.0	9.6	9.0	8.6	8.2	9.4	8.9	8.5	8.1	9.1	8.7	8.3	8.0	8.8	8.5	8.2	7.9	7.6
Hm	1.26Hm	1.26Hm	4.0	9.9	9.5	9.1	8.7	9.7	9.3	9.0	8.7	9.4	9.1	8.8	8.5	9.2	8.9	8.6	8.4	8.2
			5.0	10.1	9.7	9.4	9.1	9.9	9.6	9.3	9.0	9.6	9.4	9.1	8.9	9.4	9.2	8.9	8.8	8.5
			7.0	10.3	10.0	9.8	9.6	10.1	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.6	9.5	9.3	9.2	8.9
			10.0	10.4	10.3	10.1	9.9	10.3	10.1	10.0	9.8	10.1	9.9	9.8	9.6	9.8	9.7	9.6	9.5	9.2

