

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | XLGB1113                |
| 光源       | LLD2000VCE1 ×1 531.0 lm |
| 管理番号     | K0176313 (0) DR1        |
| BZ分類     | BZ3                     |

| 器具効率     |                     | 85 %            | 反射率    | 天井              | 80 %              |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|---------------------|-----------------|--------|-----------------|-------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|          |                     |                 |        | 壁               | 70                | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |                     |                 |        | 床               | 10 %              |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |                     |                 |        | 室指数             | 照明率 ( X0.01 ) ZCM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率      |                     | 良<br>中<br>否     | 0.67   | 0.6             | 56                | 47 | 41 | 38 | 55   | 47 | 41 | 38 | 53   | 46 | 41 | 37 | 51   | 45 | 41 | 37 | 36  |
|          |                     |                 | 0.63   | 0.8             | 64                | 56 | 50 | 47 | 63   | 55 | 50 | 46 | 61   | 54 | 50 | 46 | 59   | 53 | 49 | 46 | 45  |
|          |                     |                 | 0.56   | 1.0             | 69                | 62 | 57 | 53 | 68   | 61 | 56 | 53 | 66   | 60 | 56 | 52 | 64   | 59 | 55 | 52 | 50  |
|          |                     |                 |        | 1.25            | 73                | 67 | 62 | 58 | 72   | 66 | 62 | 58 | 70   | 65 | 61 | 58 | 68   | 63 | 60 | 57 | 56  |
| 下方投影面積   |                     | cm <sup>2</sup> |        | 1.5             | 76                | 70 | 66 | 62 | 75   | 69 | 65 | 62 | 73   | 68 | 64 | 61 | 71   | 67 | 64 | 61 | 59  |
|          |                     |                 | 等価発光面積 | cm <sup>2</sup> | 2.0               | 80 | 75 | 71 | 68   | 79 | 74 | 71 | 68   | 76 | 73 | 70 | 67   | 74 | 71 | 69 | 66  |
| 取付<br>高さ | 器具間隔最大限             |                 |        | 2.5             | 82                | 78 | 75 | 72 | 81   | 77 | 74 | 71 | 79   | 76 | 73 | 71 | 77   | 74 | 72 | 70 | 68  |
|          | 横方向 ( A ) 縦方向 ( B ) |                 |        | 3.0             | 84                | 80 | 77 | 75 | 82   | 79 | 77 | 74 | 80   | 78 | 75 | 73 | 78   | 76 | 74 | 72 | 70  |
| H m      | 1.39 H m 1.39 H m   |                 |        | 4.0             | 86                | 83 | 80 | 78 | 84   | 82 | 80 | 78 | 82   | 80 | 78 | 77 | 80   | 79 | 77 | 75 | 73  |
|          |                     |                 |        | 5.0             | 87                | 85 | 83 | 81 | 86   | 84 | 82 | 80 | 84   | 82 | 80 | 79 | 82   | 80 | 79 | 78 | 75  |
|          |                     |                 |        | 7.0             | 88                | 87 | 85 | 84 | 87   | 86 | 84 | 83 | 85   | 84 | 83 | 81 | 83   | 82 | 81 | 80 | 78  |
|          |                     |                 |        | 10.0            | 89                | 88 | 87 | 86 | 88   | 87 | 86 | 85 | 86   | 85 | 84 | 83 | 84   | 83 | 83 | 82 | 80  |

