

# 屋内照明器具特性

|         |                   |  |          |  |  |
|---------|-------------------|--|----------|--|--|
| 品番 (品名) | XAD1101L          |  |          |  |  |
| 光源      | LED2700_70_340 ×1 |  | 340.0 lm |  |  |
| 管理番号    | K0166804(0)DB1    |  |          |  |  |
| BZ分類    | BZ4/0.7/BZ3       |  |          |  |  |

|        |                 |         |      |     |     |     |     |     |     |     |     |     |     |    |     |     |    |    |    |     |
|--------|-----------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|-----|----|----|----|-----|
| 器具効率   | 100%            | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |    | 30% |     |    |    | 0% |     |
|        | 上方光束<br>0%      |         | 壁    | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10  | 70  | 50 | 30 | 10 | 0%  |
| 下方光束   | 100%            | 床       |      | 10% |     |     |     | 10% |     |     |     | 10% |     |    |     | 10% |    |    |    | 0%  |
| 室指数    | 照明率 ( X0.01 )   |         |      |     |     |     |     |     |     |     |     |     |     |    |     |     |    |    |    | ZCM |
| 保守率    | 良               | 0.67    | 0.6  | 61  | 50  | 43  | 38  | 60  | 49  | 42  | 38  | 58  | 48  | 42 | 37  | 56  | 47 | 42 | 37 | 36  |
|        | 中               | 0.63    | 0.8  | 72  | 61  | 54  | 49  | 70  | 61  | 54  | 49  | 68  | 59  | 53 | 49  | 66  | 58 | 53 | 49 | 47  |
|        | 否               | 0.56    | 1.0  | 78  | 69  | 62  | 57  | 77  | 68  | 62  | 57  | 74  | 67  | 61 | 57  | 72  | 66 | 61 | 57 | 55  |
|        |                 |         | 1.25 | 84  | 76  | 70  | 65  | 83  | 75  | 69  | 65  | 80  | 74  | 68 | 64  | 78  | 72 | 68 | 64 | 62  |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5  | 88  | 81  | 75  | 70  | 87  | 80  | 74  | 70  | 84  | 78  | 73 | 70  | 81  | 76 | 72 | 69 | 67  |
| 等価発光面積 | cm <sup>2</sup> |         | 2.0  | 93  | 87  | 82  | 78  | 92  | 86  | 82  | 78  | 89  | 84  | 80 | 77  | 86  | 82 | 79 | 76 | 74  |
| 取付高さ   | 器具間隔最大限         |         | 2.5  | 96  | 91  | 87  | 83  | 95  | 90  | 86  | 83  | 92  | 88  | 85 | 82  | 90  | 86 | 83 | 81 | 78  |
|        | 横方向 (A)         | 縦方向 (B) | 3.0  | 98  | 94  | 90  | 87  | 97  | 93  | 89  | 86  | 94  | 91  | 88 | 85  | 92  | 89 | 86 | 84 | 82  |
| Hm     | 1.25Hm          | 1.25Hm  | 4.0  | 101 | 97  | 94  | 92  | 99  | 96  | 93  | 91  | 97  | 94  | 92 | 90  | 94  | 92 | 90 | 88 | 86  |
|        |                 |         | 5.0  | 102 | 99  | 97  | 95  | 101 | 98  | 96  | 94  | 98  | 96  | 94 | 92  | 96  | 94 | 93 | 91 | 88  |
|        |                 |         | 7.0  | 104 | 102 | 100 | 98  | 103 | 101 | 99  | 97  | 100 | 99  | 97 | 96  | 98  | 97 | 95 | 94 | 91  |
|        |                 |         | 10.0 | 105 | 104 | 102 | 101 | 104 | 103 | 101 | 100 | 102 | 100 | 99 | 98  | 99  | 98 | 97 | 97 | 94  |

