

屋内照明器具特性

品番 (品名)	XAS3331V	
光源	LED3500_70_575 ×2	575.0 lm
管理番号	K0170906(1)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床	10%				10%				10%				10%				0%	
室指数			照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	85	80	76	73	85	79	76	73	83	79	76	73	82	78	75	73	72
	中	0.63	0.8	91	86	82	80	90	85	82	80	89	85	82	80	87	84	81	79	78
	否	0.56	1.0	94	90	87	84	94	89	86	84	92	88	86	84	91	87	85	83	82
下方投影面積	等価発光面積	cm ²	1.25	97	93	90	88	96	93	90	88	95	92	89	87	93	91	88	87	85
			1.5	99	96	93	91	98	95	92	90	96	94	91	90	95	92	91	89	88
取付高さ	器具間隔最大限		2.5	103	100	98	97	102	100	98	96	100	98	96	95	98	97	95	94	92
	横方向 (A)	縦方向 (B)	3.0	104	102	100	98	103	101	99	98	101	99	98	97	99	98	96	95	93
Hm	0.41Hm	0.41Hm	4.0	105	103	102	101	104	102	101	100	102	101	99	98	100	99	98	97	95
			5.0	106	104	103	102	105	103	102	101	102	101	101	100	100	100	99	98	96
			7.0	106	105	104	104	105	104	104	103	103	102	102	101	101	101	100	99	97
			10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	100	98

