

屋内照明器具特性																					
品番 (品名)	XL573PHFK																				
光源	LED3500_85_4520 x1 4520.0 lm																				
管理番号	K0162374(1)DB1																				
BZ分類	BZ4																				
器具効率	99%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	0% 99%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否	0.81	0.6	5.9	4.7	3.9	3.4	5.7	4.6	3.9	3.4	5.5	4.5	3.9	3.4	5.3	4.4	3.8	3.4	3.2	
		0.77	0.8	6.9	5.8	5.0	4.5	6.7	5.7	5.0	4.5	6.5	5.6	4.9	4.5	6.2	5.5	4.9	4.4	4.2	
		0.68	1.0	7.5	6.5	5.8	5.3	7.4	6.5	5.8	5.3	7.1	6.3	5.7	5.2	6.9	6.2	5.6	5.2	5.0	
			1.25	8.1	7.2	6.6	6.0	8.0	7.1	6.5	6.0	7.7	7.0	6.4	6.0	7.4	6.8	6.3	5.9	5.7	
下方投影面積 等価発光面積	c m ² c m ²	1.5	8.5	7.7	7.1	6.6	8.4	7.6	7.0	6.6	8.1	7.4	6.9	6.5	7.8	7.3	6.8	6.4	6.2		
		2.0	9.1	8.4	7.8	7.4	8.9	8.3	7.8	7.4	8.6	8.1	7.7	7.3	8.4	7.9	7.5	7.2	7.0		
取付高さ	器具間隔最大限		2.5	9.4	8.8	8.4	7.9	9.2	8.7	8.3	7.9	9.0	8.5	8.1	7.8	8.7	8.3	8.0	7.7	7.5	
	横方向 (A)	縦方向 (B)																			
1.5m	1.84m	1.84m	4.0	9.9	9.5	9.2	8.9	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.7	9.2	9.0	8.8	8.6	8.3	
2	2.43	2.43	5.0	10.1	9.8	9.5	9.2	9.9	9.7	9.4	9.1	9.7	9.4	9.2	9.0	9.4	9.2	9.0	8.9	8.6	
2.5	2.96	2.96	7.0	10.3	10.1	9.8	9.6	10.2	9.9	9.7	9.5	9.9	9.7	9.5	9.4	9.7	9.5	9.4	9.2	9.0	
3	3.55	3.56	10.0	10.4	10.3	10.1	10.0	10.3	10.1	10.0	9.9	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2	

