

屋内照明器具特性	
品番 (品名)	XLGB1227
光源	LLD20001CQ1 ×1 531.0 lm
管理番号	K0176322 (0) DR 1
BZ分類	BZ3

器具効率		75 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.67	0.6	49	42	37	34	49	41	37	33	47	41	36	33	46	40	36	33	32
			0.63	0.8	56	49	44	40	55	48	44	40	53	48	43	40	52	47	43	40	39
			0.56	1.0	60	54	49	45	59	53	49	45	57	52	48	45	56	51	47	45	43
				1.25	64	58	54	50	63	57	53	50	61	56	53	50	59	55	52	49	48
下方投影面積		cm ²		1.5	67	61	57	54	65	60	57	53	63	59	56	53	62	58	55	52	51
				2.0	70	66	62	59	69	65	61	59	67	63	60	58	65	62	59	57	56
取付 高さ	器具間隔最大限			2.5	72	68	65	62	71	68	65	62	69	66	64	61	67	65	62	61	59
	横方向 (A) 縦方向 (B)			3.0	74	70	67	65	73	70	67	65	71	68	66	64	69	67	65	63	61
H m	1.32 H m 1.32 H m			4.0	76	73	71	69	75	72	70	68	73	71	69	67	71	69	67	66	64
				5.0	77	75	73	71	76	74	72	70	74	72	71	69	72	71	69	68	66
				7.0	78	76	75	74	77	76	74	73	75	74	73	72	73	72	71	70	68
				10.0	79	78	77	76	78	77	76	75	76	75	74	74	74	74	73	72	70

