

屋内照明器具特性

品番 (品名)	XAS3320V	
光源	LED3500_70_690 ×2	690.0 1m
管理番号	K0170908(1)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	100%	床		10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM	
保守率	良 0.67	0.6	0.6	84	78	74	71	83	77	74	71	82	77	73	71	81	76	73	71	70	
	中 0.63		0.8	90	84	81	78	89	84	80	78	87	83	80	78	86	82	79	77	76	
	否 0.56		1.0	93	88	85	82	92	88	85	82	91	87	84	82	89	86	83	81	80	
下方投影面積	cm ²	等価発光面積	cm ²	1.25	96	92	89	86	95	91	88	86	94	90	88	86	92	89	87	85	84
				1.5	98	95	92	89	97	94	91	89	96	93	90	88	94	91	89	88	86
取付高さ	器具間隔最大限		Hm	0.41Hm	0.41Hm	2.5	102	100	98	96	101	99	97	95	99	97	96	94	93	91	
	横方向 (A)	縦方向 (B)				3.0	103	101	99	98	102	100	98	97	100	99	97	96	98	97	96
Hm	0.41Hm	0.41Hm	4.0	105	103	101	100	104	102	100	99	101	100	99	98	99	98	97	97	94	
			5.0	105	104	103	101	104	103	102	101	102	101	100	99	100	99	98	98	95	95
Hm	0.41Hm	0.41Hm	7.0	106	105	104	103	105	104	103	102	103	102	101	101	100	100	99	99	97	
			10.0	107	106	105	105	106	105	104	104	104	103	102	102	101	101	101	100	99	97

