

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | XLGB1024                |
| 光源       | LLD20003CQ1 ×1 531.0 lm |
| 管理番号     | K0176303 ( 0 ) DR 1     |
| BZ分類     | BZ2                     |

| 器具効率     |                     | 62 %            | 反射率    | 天井              | 80 %              |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|---------------------|-----------------|--------|-----------------|-------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|          |                     |                 |        | 壁               | 70                | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |                     |                 |        | 床               | 10 %              |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |                     |                 |        | 室指数             | 照明率 ( X0.01 ) ZCM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率      |                     | 良<br>中<br>否     | 0.67   | 0.6             | 41                | 35 | 31 | 29 | 41   | 35 | 31 | 29 | 39   | 34 | 31 | 28 | 38   | 34 | 31 | 28 | 27  |
|          |                     |                 | 0.63   | 0.8             | 48                | 42 | 39 | 36 | 47   | 42 | 39 | 36 | 46   | 41 | 38 | 36 | 45   | 41 | 38 | 36 | 35  |
|          |                     |                 | 0.56   | 1.0             | 52                | 47 | 44 | 41 | 51   | 47 | 43 | 41 | 50   | 46 | 43 | 41 | 48   | 45 | 42 | 40 | 39  |
|          |                     |                 |        | 1.25            | 55                | 51 | 48 | 45 | 54   | 50 | 47 | 45 | 53   | 49 | 47 | 45 | 51   | 48 | 46 | 44 | 43  |
| 下方投影面積   |                     | cm <sup>2</sup> |        | 1.5             | 57                | 53 | 50 | 48 | 56   | 53 | 50 | 48 | 55   | 52 | 49 | 47 | 53   | 51 | 49 | 47 | 46  |
|          |                     |                 | 等価発光面積 | cm <sup>2</sup> | 2.0               | 60 | 56 | 54 | 52   | 59 | 56 | 54 | 52   | 57 | 55 | 53 | 51   | 56 | 54 | 52 | 51  |
| 取付<br>高さ | 器具間隔最大限             |                 |        | 2.5             | 61                | 59 | 56 | 55 | 60   | 58 | 56 | 54 | 59   | 57 | 55 | 54 | 57   | 56 | 54 | 53 | 52  |
|          | 横方向 ( A ) 縦方向 ( B ) |                 |        | 3.0             | 62                | 60 | 58 | 56 | 61   | 59 | 58 | 56 | 60   | 58 | 57 | 55 | 58   | 57 | 56 | 55 | 53  |
| H m      | 1.28 H m 1.28 H m   |                 |        | 4.0             | 63                | 62 | 60 | 59 | 63   | 61 | 60 | 58 | 61   | 60 | 59 | 58 | 60   | 59 | 58 | 57 | 55  |
|          |                     |                 |        | 5.0             | 64                | 63 | 61 | 60 | 63   | 62 | 61 | 60 | 62   | 61 | 60 | 59 | 60   | 60 | 59 | 58 | 56  |
|          |                     |                 |        | 7.0             | 65                | 64 | 63 | 62 | 64   | 63 | 62 | 62 | 63   | 62 | 61 | 61 | 61   | 61 | 60 | 60 | 58  |
|          |                     |                 |        | 10.0            | 66                | 65 | 64 | 64 | 65   | 64 | 64 | 63 | 63   | 63 | 62 | 62 | 62   | 62 | 61 | 61 | 59  |

