

屋内照明器具特性

品番 (品名)	L S E W4 0 7 0									
光源	LED2700_70_515 x1					515.0 lm				
管理番号	K0171392(0)DB1									
BZ分類	BZ9/0.9/BZ8									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		51%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		49%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	c m ²		1.25	64	54	45	39	59	49	42	36	48	41	35	30	39	33	29	25	16	
	等価発光面積	c m ²		1.5	69	58	50	44	63	54	47	41	52	45	39	34	42	36	32	28	18
取付高さ		器具間隔最大限		2.5	78	70	63	58	72	65	59	54	60	54	50	45	48	44	41	38	25
	H m	横方向 (A)	縦方向 (B)	3.0	80	73	67	62	74	68	62	58	62	57	53	49	51	47	44	41	27
1.62 H m		1.86 H m	4.0	84	78	73	68	77	72	68	64	65	61	57	54	53	50	48	45	31	
			5.0	86	81	77	73	80	75	71	68	67	64	60	58	55	53	50	48	33	
			7.0	89	85	81	78	82	79	76	73	70	67	64	62	58	56	54	52	36	
			10.0	91	88	85	83	84	82	79	77	72	70	68	66	60	58	57	55	39	

