

# 屋内照明器具特性

|         |                             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|-----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XAS1502V                    |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED3500_70_420 x1 420.0 l m |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0170907(0)DB1              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ4/1.1/BZ3/3.5/BZ4         |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                                     |          |      |                  |     |     |     |     |     |     |     |     |     |    |     |     |    |    |    |    |
|--------|-------------------------------------|----------|------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|-----|----|----|----|----|
| 器具効率   | 100%                                | 天井       | 80%  |                  |     |     | 70% |     |     |     | 50% |     |     |    | 30% |     |    |    | 0% |    |
|        |                                     |          | 壁    | 70               | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10  | 70  | 50 | 30 | 10 | 0% |
| 上方光束   | 0%                                  | 反射率      | 床    | 10%              |     |     |     | 10% |     |     |     | 10% |     |    |     | 10% |    |    |    | 0% |
| 下方光束   | 100%                                |          | 室指数  | 照明率 ( X0.01) ZCM |     |     |     |     |     |     |     |     |     |    |     |     |    |    |    |    |
| 保守率    | 良<br>中<br>否<br>0.67<br>0.63<br>0.56 | 0.6      | 60   | 49               | 41  | 36  | 59  | 48  | 41  | 36  | 57  | 47  | 41  | 36 | 55  | 46  | 40 | 36 | 34 |    |
|        |                                     | 0.8      | 71   | 60               | 53  | 48  | 69  | 59  | 53  | 48  | 67  | 58  | 52  | 47 | 64  | 57  | 51 | 47 | 45 |    |
|        |                                     | 1.0      | 77   | 68               | 61  | 56  | 76  | 67  | 60  | 56  | 73  | 65  | 60  | 55 | 71  | 64  | 59 | 55 | 53 |    |
|        |                                     | 1.25     | 83   | 75               | 68  | 63  | 82  | 74  | 68  | 63  | 79  | 72  | 67  | 63 | 76  | 71  | 66 | 62 | 60 |    |
| 下方投影面積 | c m <sup>2</sup>                    | 1.5      | 87   | 79               | 74  | 69  | 86  | 79  | 73  | 68  | 83  | 77  | 72  | 68 | 80  | 75  | 71 | 67 | 65 |    |
|        |                                     | 2.0      | 92   | 86               | 81  | 77  | 91  | 85  | 80  | 76  | 88  | 83  | 79  | 75 | 85  | 81  | 78 | 75 | 72 |    |
| 取付高さ   | 器具間隔最大限                             |          | 2.5  | 95               | 90  | 86  | 82  | 94  | 89  | 85  | 81  | 91  | 87  | 83 | 80  | 88  | 85 | 82 | 79 | 77 |
|        | 横方向 (A)                             | 縦方向 (B)  | 3.0  | 97               | 93  | 89  | 86  | 96  | 92  | 88  | 85  | 93  | 90  | 87 | 84  | 91  | 88 | 85 | 83 | 80 |
| H m    | 1.29 H m                            | 1.29 H m | 4.0  | 100              | 97  | 93  | 90  | 99  | 95  | 92  | 90  | 96  | 93  | 91 | 88  | 94  | 91 | 89 | 87 | 85 |
|        |                                     |          | 5.0  | 102              | 99  | 96  | 94  | 100 | 98  | 95  | 93  | 98  | 95  | 93 | 91  | 95  | 93 | 92 | 90 | 87 |
|        |                                     |          | 7.0  | 104              | 101 | 99  | 97  | 102 | 100 | 98  | 97  | 100 | 98  | 96 | 95  | 97  | 96 | 95 | 93 | 90 |
|        |                                     |          | 10.0 | 105              | 103 | 102 | 100 | 104 | 102 | 101 | 100 | 101 | 100 | 99 | 98  | 99  | 98 | 97 | 96 | 93 |

