

# 屋内照明器具特性

|         |                                   |           |
|---------|-----------------------------------|-----------|
| 品番 (品名) | L G W C 8 0 3 6 4                 |           |
| 光源      | LED2700_70_265 ×1                 | 265.0 l m |
| 管理番号    | K0171393 ( 0 ) DB 1               |           |
| B Z 分類  | B Z 6 / 1.4 / B Z 5 / 1.8 / B Z 6 |           |

|        |                                    |           |      |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |       |
|--------|------------------------------------|-----------|------|------|----|----|------|------|----|----|------|------|----|----|------|------|----|----|-----|-----|-------|
| 器具効率   | 100 %                              | 天井        | 80 % |      |    |    | 70 % |      |    |    | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |       |
|        | 上方光束<br>51 %                       |           | 反射率  | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10  | 0 % |       |
| 下方光束   | 49 %                               | 床         |      | 10 % |    |    |      | 10 % |    |    |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |       |
| 室指数    | 照明率 ( X 0.01 )                     |           |      |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     | Z C M |
| 保守率    | 良<br>中<br>否<br>0.63<br>0.6<br>0.56 | 0.6       | 48   | 37   | 29 | 24 | 44   | 34   | 27 | 23 | 37   | 29   | 24 | 20 | 30   | 24   | 20 | 17 | 12  |     |       |
|        |                                    | 0.8       | 57   | 46   | 38 | 33 | 52   | 42   | 36 | 31 | 44   | 36   | 31 | 27 | 36   | 30   | 26 | 23 | 16  |     |       |
|        |                                    | 1.0       | 63   | 52   | 45 | 39 | 58   | 49   | 42 | 37 | 49   | 41   | 36 | 32 | 40   | 35   | 31 | 27 | 19  |     |       |
|        |                                    | 1.25      | 68   | 59   | 52 | 46 | 63   | 55   | 48 | 43 | 53   | 46   | 41 | 37 | 44   | 39   | 35 | 32 | 23  |     |       |
| 下方投影面積 | c m <sup>2</sup>                   | 1.5       | 72   | 64   | 57 | 51 | 67   | 59   | 53 | 48 | 56   | 50   | 45 | 42 | 46   | 42   | 38 | 35 | 25  |     |       |
|        |                                    | 2.0       | 78   | 70   | 64 | 59 | 72   | 65   | 60 | 55 | 61   | 56   | 51 | 48 | 50   | 46   | 43 | 41 | 29  |     |       |
| 取付高さ   | 器具間隔最大限                            |           | 2.5  | 81   | 75 | 69 | 64   | 75   | 69 | 64 | 60   | 63   | 59 | 55 | 52   | 53   | 49 | 47 | 32  |     |       |
|        | 横方向 ( A )                          | 縦方向 ( B ) | 3.0  | 84   | 78 | 73 | 69   | 77   | 72 | 68 | 64   | 65   | 62 | 58 | 55   | 54   | 52 | 49 | 34  |     |       |
| H m    | 1.37 H m                           | 1.29 H m  | 4.0  | 87   | 82 | 78 | 74   | 80   | 76 | 73 | 69   | 68   | 65 | 62 | 60   | 57   | 55 | 52 | 37  |     |       |
|        |                                    |           | 5.0  | 89   | 85 | 81 | 78   | 82   | 79 | 76 | 73   | 70   | 67 | 65 | 63   | 58   | 56 | 55 | 39  |     |       |
|        |                                    |           | 7.0  | 91   | 88 | 85 | 83   | 84   | 82 | 79 | 77   | 72   | 70 | 68 | 66   | 60   | 59 | 57 | 41  |     |       |
|        |                                    |           | 10.0 | 93   | 90 | 88 | 86   | 86   | 84 | 82 | 81   | 74   | 72 | 71 | 69   | 62   | 61 | 60 | 43  |     |       |

