

屋内照明器具特性	
品番 (品名)	XLGB3010
光源	LLD2000MNCE1 ×1 531.0 lm
管理番号	K0175638 (0) DR 1
BZ分類	BZ5 / 0.7 / BZ4

器具効率		90 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																
保守率		良 中 否	0.67	0.6	53	42	35	30	51	41	35	30	49	40	34	30	47	39	34	30	28
			0.63	0.8	62	52	45	40	61	51	45	40	58	50	44	40	56	49	43	39	38
			0.56	1.0	68	59	52	47	67	58	52	47	64	57	51	47	62	55	50	46	44
				1.25	73	65	59	54	72	64	58	54	69	63	58	53	67	61	57	53	51
下方投影面積		cm ²		1.5	77	70	64	59	76	69	63	59	73	67	62	58	71	65	61	58	56
			等価発光面積	cm ²	2.0	82	76	71	67	81	75	70	66	78	73	69	66	76	71	68	65
取付 高さ	器具間隔最大限			2.5	85	80	76	72	84	79	75	71	81	77	74	70	79	75	72	70	67
	横方向 (A) 縦方向 (B)			3.0	87	83	79	76	86	82	78	75	83	80	77	74	81	78	75	73	71
H m	1.27 H m	1.27 H m		4.0	90	86	83	80	89	85	82	80	86	83	81	79	84	82	79	78	75
				5.0	92	89	86	84	90	88	85	83	88	86	84	82	86	84	82	80	78
				7.0	93	91	89	87	92	90	88	87	90	88	87	85	88	86	85	84	81
				10.0	95	93	92	90	94	92	91	89	91	90	89	88	89	88	87	86	84

