

屋内照明器具特性	
品番 (品名)	XLGB3051
光源	LLD2000VCE1 ×1 531.0 lm
管理番号	K0175645 (0) DR 1
BZ分類	BZ4

器具効率		81 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率	良 中 否	0.67	0.6	48	38	32	28	47	38	32	28	45	37	32	28	43	36	31	28	26	
		0.63	0.8	56	47	41	37	55	47	41	37	53	46	41	37	51	45	40	37	35	
		0.56	1.0	62	54	48	43	60	53	47	43	58	52	47	43	56	51	46	43	41	
			1.25	67	59	54	50	65	59	54	50	63	57	53	49	61	56	52	49	47	
下方投影面積		cm ²	1.5	70	63	58	54	69	63	58	54	66	61	57	54	64	60	56	53	51	
等価発光面積			cm ²	2.0	74	69	65	61	73	68	64	61	71	67	63	60	69	65	62	59	58
取付 高さ	器具間隔最大限		2.5	77	72	69	66	76	72	68	65	73	70	67	64	71	68	66	64	62	
	横方向 (A) 縦方向 (B)		3.0	79	75	72	69	78	74	71	68	75	72	70	67	73	71	69	67	65	
H m	1.24 H m	1.24 H m	4.0	81	78	75	73	80	77	75	73	78	75	73	71	76	74	72	70	68	
			5.0	82	80	78	76	81	79	77	75	79	77	76	74	77	76	74	73	71	
			7.0	84	82	80	79	83	81	80	78	81	79	78	77	79	78	77	76	73	
			10.0	85	84	83	81	84	83	82	81	82	81	80	79	80	79	79	78	76	

