

屋内照明器具特性	
品番 (品名)	XL574ZPTK
光源	LED3000_85_5530 x1 5530.0 lm
管理番号	K0162373 (1) DB 1
BZ分類	BZ3

器具効率	99 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	99 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.81 0.77 0.68	0.6	63	52	45	40	62	51	45	40	59	51	44	40	58	50	44	40	38	
		0.8	73	63	56	52	72	62	56	51	69	61	55	51	67	60	55	51	49	
		1.0	79	70	64	59	78	70	64	59	75	68	63	59	73	67	62	58	56	
		1.25	85	77	71	66	83	76	70	66	81	74	69	65	78	73	68	65	63	
下方投影面積	c m ²	1.5	88	81	75	71	87	80	75	71	84	78	74	70	82	77	73	69	67	
		2.0	93	87	82	78	91	86	81	78	89	84	80	77	86	82	79	76	74	
取付高さ	器具間隔最大限		2.5	96	91	86	83	94	90	86	82	92	88	84	81	89	86	83	80	78
	横方向 (A)	縦方向 (B)	3.0	98	93	90	86	96	92	89	86	94	90	87	85	91	88	86	84	81
1.5m	1.89 m	1.89 m	4.0	100	97	94	91	99	96	93	90	96	94	91	89	94	92	90	88	85
2	2.52	2.51	5.0	102	99	96	94	100	98	95	93	98	96	94	92	95	94	92	90	88
2.5	3.07	3.06	7.0	103	101	99	98	102	100	98	97	100	98	96	95	97	96	95	93	91
3	3.69	3.67	10.0	105	103	102	100	103	102	101	99	101	100	99	98	99	98	97	96	93

