

# 屋内照明器具特性

|         |                   |          |
|---------|-------------------|----------|
| 品番 (品名) | XAS1332L          |          |
| 光源      | LED2700_70_440 ×2 | 440.0 lm |
| 管理番号    | K0171220(1)DB1    |          |
| BZ分類    | BZ1               |          |

|                  |                 |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |
|------------------|-----------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|
| 器具効率             | 100%            | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |    | 0% |
|                  | 上方光束<br>1%      |         | 反射率  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10 |
| 下方光束<br>99%      |                 | 床       |      | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |    |    |
| 室指数              | 照明率 ( X0.01 )   |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |    |
| 保守率              | 良 0.67          | 0.6     | 84   | 78  | 74  | 71  | 83  | 77  | 73  | 71  | 81  | 76  | 73  | 71  | 80  | 76  | 73  | 71 | 69 |
|                  | 中 0.63          | 0.8     | 89   | 84  | 80  | 78  | 89  | 83  | 80  | 77  | 87  | 83  | 79  | 77  | 86  | 82  | 79  | 77 | 76 |
|                  | 否 0.56          | 1.0     | 93   | 88  | 85  | 82  | 92  | 88  | 84  | 82  | 90  | 86  | 84  | 81  | 89  | 85  | 83  | 81 | 79 |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> | 1.25    | 96   | 92  | 88  | 86  | 95  | 91  | 88  | 86  | 93  | 90  | 87  | 85  | 91  | 89  | 86  | 84 | 83 |
|                  | cm <sup>2</sup> | 1.5     | 98   | 94  | 91  | 89  | 97  | 93  | 91  | 88  | 95  | 92  | 90  | 88  | 93  | 91  | 89  | 87 | 85 |
| 取付高さ             | 器具間隔最大限         |         | 2.5  | 102 | 99  | 97  | 95  | 101 | 98  | 96  | 94  | 99  | 97  | 95  | 93  | 97  | 95  | 94 | 92 |
|                  | 横方向 (A)         | 縦方向 (B) | 3.0  | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 96  | 95  | 98  | 96  | 95 | 94 |
| Hm               | 0.41Hm          | 0.41Hm  | 4.0  | 104 | 102 | 101 | 99  | 103 | 101 | 100 | 99  | 101 | 100 | 98  | 97  | 99  | 98  | 97 | 96 |
|                  |                 |         | 5.0  | 105 | 104 | 102 | 101 | 104 | 103 | 101 | 100 | 102 | 101 | 99  | 99  | 100 | 99  | 98 | 97 |
|                  |                 |         | 7.0  | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 102 | 102 | 101 | 100 | 100 | 99  | 98 | 96 |
|                  |                 |         | 10.0 | 107 | 106 | 105 | 104 | 105 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 100 | 99 | 97 |

