

| 屋内照明器具特性 |                                                 |
|----------|-------------------------------------------------|
| 品番 (品名)  | L G W4 1 0 0 2                                  |
| 光源       | L L D4 0 0 0 1 C Q1 ×1 845.0 l m                |
| 管理番号     | K0176343 ( 0 ) D R 1                            |
| B Z 分類   | B Z 3 / 0.9 / B Z 2 / 4.5 / B Z 3 / 6.0 / B Z 2 |

| 器具効率     |                     | 58 %             | 反射率              | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |       |
|----------|---------------------|------------------|------------------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|-------|
|          |                     |                  |                  | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |       |
|          |                     |                  |                  | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |       |
| 上方光束     |                     | 0 %              | 室指数              | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     | Z C M |
| 下方光束     |                     | 58 %             |                  |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |       |
| 保守率      |                     | 良<br>中<br>否      | 0.63             | 0.6           | 37   | 31 | 28 | 25 | 37   | 31 | 27 | 25 | 36   | 31 | 27 | 25 | 35   | 30 | 27 | 25 | 24  |       |
|          |                     |                  | 0.6              | 0.8           | 43   | 38 | 34 | 32 | 43   | 38 | 34 | 32 | 41   | 37 | 34 | 31 | 40   | 36 | 33 | 31 | 30  |       |
|          |                     |                  |                  | 1.0           | 47   | 42 | 39 | 36 | 46   | 42 | 39 | 36 | 45   | 41 | 38 | 36 | 44   | 40 | 38 | 36 | 35  |       |
|          |                     |                  | 0.56             | 1.25          | 50   | 46 | 43 | 40 | 50   | 46 | 43 | 40 | 48   | 45 | 42 | 40 | 47   | 44 | 42 | 40 | 39  |       |
| 下方投影面積   |                     | c m <sup>2</sup> |                  | 1.5           | 52   | 49 | 46 | 43 | 52   | 48 | 45 | 43 | 50   | 47 | 45 | 43 | 49   | 46 | 44 | 42 | 41  |       |
| 等価発光面積   |                     |                  | c m <sup>2</sup> | 2.0           | 55   | 52 | 49 | 47 | 54   | 51 | 49 | 47 | 53   | 50 | 48 | 47 | 51   | 49 | 48 | 46 | 45  |       |
| 取付<br>高さ | 器具間隔最大限             |                  | 2.5              | 56            | 54   | 52 | 50 | 56 | 53   | 51 | 50 | 54 | 52   | 51 | 49 | 53 | 51   | 50 | 48 | 47 |     |       |
|          | 横方向 ( A ) 縦方向 ( B ) |                  | 3.0              | 58            | 55   | 53 | 52 | 57 | 55   | 53 | 51 | 55 | 54   | 52 | 51 | 54 | 53   | 51 | 50 | 49 |     |       |
| H m      | 1.17 H m            | 1.17 H m         | 4.0              | 59            | 57   | 56 | 54 | 58 | 57   | 55 | 54 | 57 | 55   | 54 | 53 | 55 | 54   | 53 | 52 | 51 |     |       |
|          |                     |                  | 5.0              | 60            | 58   | 57 | 56 | 59 | 58   | 56 | 55 | 57 | 56   | 55 | 54 | 56 | 55   | 54 | 54 | 52 |     |       |
|          |                     |                  | 7.0              | 60            | 59   | 58 | 58 | 60 | 59   | 58 | 57 | 58 | 58   | 57 | 56 | 57 | 56   | 56 | 55 | 54 |     |       |
|          |                     |                  | 10.0             | 61            | 60   | 60 | 59 | 60 | 60   | 59 | 58 | 59 | 58   | 58 | 57 | 58 | 57   | 57 | 56 | 55 |     |       |

