

屋内照明器具特性	
品番 (品名)	XLGE1007
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0176341 (0) DR 1
BZ分類	BZ3/0.9/BZ2/4.5/BZ3/6.0/BZ2

器具効率		68 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	44	37	32	29	43	36	32	29	42	36	32	29	40	35	32	29	28
			0.6	0.8	51	45	40	37	50	44	40	37	48	43	40	37	47	43	39	37	35
			0.56	1.0	55	50	46	42	54	49	45	42	53	48	45	42	51	47	44	42	41
				1.25	59	54	50	47	58	53	50	47	56	52	49	47	55	51	49	46	45
下方投影面積 等価発光面積		cm ² cm ²		1.5	61	57	53	51	60	56	53	50	59	55	52	50	57	54	52	50	48
				2.0	64	61	58	55	63	60	57	55	62	59	56	54	60	58	56	54	53
				2.5	66	63	61	58	65	62	60	58	64	61	59	57	62	60	58	57	55
				3.0	67	65	63	61	66	64	62	60	65	63	61	59	63	62	60	59	57
H _m	1.17H _m	1.17H _m		4.0	69	67	65	63	68	66	64	63	66	65	63	62	65	63	62	61	60
				5.0	70	68	67	65	69	67	66	65	67	66	65	64	66	65	64	63	61
				7.0	71	70	68	67	70	69	68	67	68	67	67	66	67	66	65	65	63
				10.0	72	71	70	69	71	70	69	68	69	68	68	67	68	67	67	66	64

