

屋内照明器具特性	
品番 (品名)	XLGE1128
光源	L LD3020VCE1 ×1 795.0 lm
管理番号	K0176345 (0) DR 1
B Z 分類	BZ1

器具効率		89 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		0 %	室指数	照明率 (X0.01)																		Z C M
下方光束		89 %																				
保守率		良	0.6	76	70	67	65	75	70	67	65	74	70	67	65	73	69	66	65	64		
		中	0.6	81	76	73	71	80	76	73	71	79	75	72	70	78	74	72	70	69		
		否	1.0	84	80	77	75	83	79	77	75	82	79	76	74	81	78	76	74	73		
		0.56	1.25	87	83	80	78	86	82	80	78	84	81	79	77	83	80	79	77	76		
下方投影面積		c m ²	1.5	88	85	83	81	87	84	82	80	86	83	81	80	84	82	81	79	78		
等価発光面積			c m ²	2.0	90	88	86	84	90	87	85	84	88	86	84	83	86	85	83	82	80	
取付高さ	器具間隔最大限		2.5	92	89	88	86	91	89	87	86	89	87	86	85	87	86	85	84	82		
	横方向 (A)		縦方向 (B)	3.0	93	91	89	88	92	90	88	87	90	88	87	86	88	87	86	85	83	
H m	0.41 H m	0.41 H m	4.0	94	92	91	90	93	91	90	89	91	90	89	88	89	88	87	87	85		
			5.0	94	93	92	91	93	92	91	90	91	90	90	89	90	89	88	88	85		
			7.0	95	94	93	92	94	93	92	92	92	91	91	90	90	90	89	89	86		
			10.0	95	95	94	94	94	94	93	93	92	92	92	91	91	90	90	90	87		

