

屋内照明器具特性	
品番 (品名)	L G W C 8 5 0 7 6 B
光源	LDA4L-H-E17/S/4 ×1 440.0 lm
管理番号	K0125801(1)DB1
BZ分類	BZ10/0.7/BZ9

器具効率	32%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	14%	床	10%				10%				10%				10%				0%	
下方光束	18%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	14	9	7	5	12	9	6	5	10	7	5	4	8	6	4	3	2	
	中 0.6	0.8	16	12	9	7	15	11	9	7	12	9	7	6	10	8	6	5	3	
	否 0.56	1.0	18	14	11	9	17	13	10	8	14	11	9	7	11	9	7	6	4	
		1.25	20	16	13	11	18	15	12	10	15	13	10	9	12	10	9	7	5	
下方投影面積	cm ²	1.5	21	18	15	13	19	16	14	12	16	14	12	10	13	11	10	8	6	
		2.0	23	20	17	15	21	18	16	14	18	16	14	12	15	13	12	10	7	
取付高さ	器具間隔最大限		2.5	24	21	19	17	22	20	18	16	19	17	15	14	16	14	13	12	8
	横方向 (A)	縦方向 (B)	3.0	25	23	20	19	23	21	19	17	20	18	16	15	17	15	14	13	9
Hm	0.00Hm	1.44Hm	4.0	26	24	22	21	24	23	21	19	21	19	18	17	18	16	15	14	10
			5.0	27	25	24	22	25	24	22	21	22	20	19	18	18	17	16	15	11
			7.0	28	27	25	24	26	25	24	23	23	22	21	20	19	18	18	17	13
			10.0	29	28	27	26	27	26	25	24	23	23	22	21	20	19	19	18	14

