

屋内照明器具特性	
品番 (品名)	L G W C 8 5 2 2 0 Z
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m
管理番号	K0168590(0)DB1
BZ分類	BZ8/0.7/BZ7

器具効率	53%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	10%	床	10%				10%				10%				10%				0%	
下方光束	43%		10%				10%				10%				10%				0%	
		室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	2.5	1.8	1.4	1.1	2.4	1.7	1.3	1.0	2.2	1.6	1.2	1.0	1.9	1.5	1.1	9	7
	中	0.6	0.8	3.0	2.3	1.8	1.5	2.8	2.2	1.8	1.4	2.6	2.0	1.6	1.3	2.3	1.9	1.5	13	10
	否	0.56	1.0	3.3	2.7	2.2	1.8	3.2	2.5	2.1	1.8	2.8	2.3	1.9	1.6	2.6	2.1	1.8	15	13
			1.25	3.6	3.0	2.5	2.2	3.5	2.9	2.4	2.1	3.1	2.6	2.3	2.0	2.8	2.4	2.1	18	16
下方投影面積		cm <sup>2</sup>	1.5	3.9	3.3	2.8	2.4	3.7	3.1	2.7	2.4	3.3	2.9	2.5	2.2	3.0	2.6	2.3	2.1	18
等価発光面積		cm <sup>2</sup>	2.0	4.2	3.7	3.2	2.9	4.0	3.5	3.1	2.8	3.6	3.2	2.9	2.6	3.3	3.0	2.7	2.4	2.1
取付高さ	器具間隔最大限		2.5	4.4	3.9	3.5	3.2	4.2	3.8	3.4	3.1	3.8	3.5	3.2	2.9	3.5	3.2	2.9	2.7	2.3
	横方向 (A)	縦方向 (B)	3.0	4.5	4.1	3.8	3.4	4.3	4.0	3.6	3.3	4.0	3.6	3.4	3.1	3.6	3.3	3.1	2.9	2.5
Hm	1.49Hm	1.49Hm	4.0	4.7	4.4	4.1	3.8	4.5	4.2	3.9	3.7	4.2	3.9	3.7	3.4	3.8	3.6	3.4	3.2	2.8
			5.0	4.9	4.6	4.3	4.0	4.7	4.4	4.1	3.9	4.3	4.1	3.9	3.7	3.9	3.7	3.6	3.4	3.0
			7.0	5.0	4.8	4.6	4.4	4.8	4.6	4.4	4.2	4.4	4.3	4.1	3.9	4.1	4.0	3.8	3.7	3.3
			10.0	5.1	5.0	4.8	4.6	4.9	4.8	4.6	4.5	4.6	4.4	4.3	4.2	4.2	4.1	4.0	3.9	3.5

