

# 屋内照明器具特性

品番 (品名)	L G W C 8 5 2 2 6 B	
光源	LDC3L-E17/C2 ×1	280.0 lm
管理番号	K0196364(0)DR1	
BZ分類	BZ10	

器具効率	67%	天井	80%				70%				50%				30%				0%		
	上方光束		41%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	26%	床	10%				10%				10%				10%				0%		
室指数			照明率 ( X0.01 )																ZCM		
保守率	良	0.63	0.6	28	19	14	10	25	17	12	9	19	13	9	7	14	10	7	4	0	
	中	0.6	0.8	33	24	19	14	29	22	17	13	23	17	13	10	17	12	9	7	2	
	否	0.56	1.0	37	28	23	18	33	26	20	16	25	20	16	13	19	15	11	9	3	
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	40	32	27	22	36	29	24	20	28	23	19	15	21	17	14	11	4	
			1.5	43	36	30	25	38	32	27	23	30	25	21	18	22	19	16	13	5	
取付高さ	器具間隔最大限		2.0	47	40	35	31	42	36	32	28	33	29	25	22	25	22	19	16	8	
	横方向 (A)	縦方向 (B)	2.5	49	44	39	35	44	39	35	31	35	31	28	25	27	24	21	19	9	
H <sub>m</sub>	H <sub>m</sub>	H <sub>m</sub>	3.0	51	46	41	38	46	42	38	34	37	33	30	27	28	25	23	21	11	
			4.0	54	49	45	42	48	45	41	38	39	36	33	31	30	28	26	24	13	
			5.0	55	51	48	45	50	47	44	41	40	38	35	33	31	29	27	26	14	
			7.0	57	54	51	49	52	49	47	45	42	40	38	36	33	31	30	28	17	
			10.0	59	56	54	52	54	52	50	48	44	42	41	39	34	33	32	31	19	

