

屋内照明器具特性	
品番 (品名)	L G B 1 5 0 3 1 B F
光源	L D A 7 L - D - G / S / Z 6 × 1 8 1 0 . 0 l m
管理番号	K 0 1 2 6 4 8 5 (0) D B 1
B Z 分類	B Z 8

器具効率		9 1 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		3 8 %	室指数	照明率 (X 0 . 0 1)																	Z C M
下方光束		5 3 %																			
保守率		良	0 . 6 3	0 . 6	4 2	3 0	2 3	1 8	3 8	2 8	2 2	1 7	3 3	2 4	1 9	1 5	2 7	2 1	1 6	1 2	8
		中	0 . 6	0 . 8	4 9	3 8	3 0	2 5	4 6	3 5	2 8	2 3	3 9	3 0	2 5	2 0	3 2	2 6	2 1	1 7	1 2
		否	0 . 5 6	1 . 0	5 5	4 4	3 6	3 0	5 0	4 1	3 4	2 8	4 3	3 5	2 9	2 5	3 6	3 0	2 5	2 1	1 5
		1 . 2 5	6 0	5 0	4 2	3 6	5 5	4 6	3 9	3 4	4 7	4 0	3 4	3 0	3 9	3 4	2 9	2 5	1 8		
下方投影面積		c m ²		1 . 5	6 3	5 4	4 6	4 1	5 9	5 0	4 4	3 8	5 0	4 3	3 8	3 3	4 2	3 7	3 2	2 9	2 1
等価発光面積		c m ²		2 . 0	6 8	6 0	5 3	4 8	6 3	5 6	5 0	4 5	5 4	4 8	4 3	3 9	4 6	4 1	3 7	3 4	2 5
取付 高さ	器具間隔最大限		2 . 5	7 2	6 4	5 8	5 3	6 7	6 0	5 5	5 0	5 7	5 2	4 7	4 4	4 8	4 4	4 1	3 7	2 8	
	横方向 (A)		縦方向 (B)		3 . 0	7 4	6 8	6 2	5 7	6 9	6 3	5 8	5 4	5 9	5 5	5 1	4 7	5 0	4 7	4 3	4 0
H m	1 . 5 0 H m	1 . 5 0 H m	4 . 0	7 7	7 2	6 7	6 3	7 2	6 7	6 3	5 9	6 2	5 8	5 5	5 2	5 3	5 0	4 7	4 5	3 4	
			5 . 0	7 9	7 5	7 0	6 6	7 4	7 0	6 6	6 3	6 4	6 1	5 8	5 5	5 5	5 2	5 0	4 8	3 6	
			7 . 0	8 2	7 8	7 5	7 1	7 7	7 3	7 0	6 7	6 7	6 4	6 1	5 9	5 7	5 5	5 3	5 1	3 9	
			1 0 . 0	8 4	8 1	7 8	7 6	7 9	7 6	7 4	7 1	6 9	6 7	6 5	6 3	5 9	5 8	5 6	5 5	4 2	

