

屋内照明器具特性	
品番 (品名)	LGB19300F
光源	LDA7L-D-G/S/Z6 ×3 810.0 lm
管理番号	K0172630(0)DB1
BZ分類	BZ6

器具効率		8 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		2 9 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		5 3 %																					
保守率		良 中 否	0 . 6 7	0 . 6	4 1	3 1	2 5	2 1	3 9	3 0	2 4	2 0	3 4	2 7	2 2	1 8	3 0	2 4	2 0	1 7	1 3		
			0 . 6 3	0 . 8	4 8	3 9	3 2	2 8	4 5	3 7	3 1	2 6	4 0	3 3	2 8	2 4	3 5	2 9	2 5	2 2	1 8		
			0 . 5 6	1 . 0	5 3	4 4	3 8	3 3	5 0	4 2	3 6	3 1	4 4	3 7	3 2	2 8	3 8	3 3	2 9	2 6	2 1		
				1 . 2 5	5 7	4 9	4 3	3 8	5 4	4 6	4 1	3 6	4 7	4 1	3 7	3 3	4 1	3 6	3 3	3 0	2 4		
下方投影面積		c m ²	1 . 5	6 1	5 3	4 7	4 2	5 7	5 0	4 4	4 0	5 0	4 4	4 0	3 6	4 3	3 9	3 6	3 3	2 6			
等価発光面積			c m ²	2 . 0	6 5	5 8	5 3	4 8	6 1	5 5	5 0	4 6	5 4	4 9	4 5	4 1	4 7	4 3	4 0	3 7	3 0		
取付 高さ	器具間隔最大限		2 . 5	6 8	6 2	5 7	5 3	6 4	5 8	5 4	5 0	5 6	5 2	4 8	4 5	4 9	4 6	4 3	4 0	3 3			
	横方向 (A)		縦方向 (B)	3 . 0	7 0	6 4	6 0	5 6	6 6	6 1	5 7	5 3	5 8	5 4	5 1	4 8	5 1	4 8	4 5	4 3	3 5		
H m	1 . 2 1 H m	1 . 2 5 H m	4 . 0	7 2	6 8	6 4	6 1	6 8	6 4	6 1	5 8	6 0	5 7	5 5	5 2	5 3	5 1	4 8	4 6	3 8			
			5 . 0	7 4	7 0	6 7	6 4	7 0	6 7	6 4	6 1	6 2	5 9	5 7	5 5	5 5	5 3	5 1	4 9	4 0			
			7 . 0	7 6	7 3	7 0	6 8	7 2	6 9	6 7	6 5	6 4	6 2	6 0	5 8	5 7	5 5	5 3	5 2	4 2			
			1 0 . 0	7 8	7 5	7 3	7 1	7 4	7 2	7 0	6 8	6 6	6 4	6 3	6 1	5 8	5 7	5 6	5 5	4 5			

