

屋内照明器具特性	
品番 (品名)	LGB57322K
光源	LDA7L-D-G/S/Z6 ×3 810.0 lm
管理番号	K0166334 (0) DB1
BZ分類	BZ6

器具効率		90 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		26 % 64 %	室指数	照明率 (X0.01) ZCM																	
保守率		良 中 否	0.67	0.6	45	34	27	22	42	32	26	21	38	29	24	20	34	27	22	18	15
			0.63	0.8	53	42	35	30	50	40	34	29	45	37	31	27	40	33	28	25	20
			0.56	1.0	58	48	41	35	55	46	39	34	49	42	36	32	44	38	33	29	24
			1.25	63	54	47	41	60	52	45	40	54	47	41	37	48	42	38	34	29	
下方投影面積		cm ²	1.5	67	58	52	46	64	56	49	44	57	50	45	41	51	46	41	38	32	
等価発光面積			cm ²	2.0	72	65	58	53	68	62	56	51	61	56	51	47	55	50	47	43	37
取付高さ				器具間隔最大限		2.5	75	69	63	58	71	66	60	56	64	60	55	52	58	54	50
H m		1.25 H m	縦方向 (B)	3.0	78	72	67	62	74	68	64	60	66	62	58	55	60	56	53	51	43
H m		1.25 H m		4.0	81	76	71	68	77	72	69	65	69	66	63	60	62	60	57	55	47
				5.0	82	78	75	71	79	75	72	68	71	68	65	63	64	62	60	58	49
				7.0	85	82	79	76	81	78	75	73	73	71	69	67	66	65	63	61	52
				10.0	87	84	82	80	83	81	78	77	75	74	72	70	68	67	66	64	55

