

屋内照明器具特性	
品番 (品名)	L G B 1 9 3 4 1 W F
光源	L D A 7 L - D - G / S / Z 6 × 3 8 1 0 . 0 l m
管理番号	K 0 1 2 6 4 7 2 (0) D B 1
B Z 分類	B Z 8

器具効率		9 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
				室指数	照明率 (X 0 . 0 1) Z C M																			
保守率		良 中 否	0 . 6 3	0 . 6	1 . 0	0 . 5 6	0 . 6	4 1	3 0	2 3	1 8	3 8	2 8	2 1	1 7	3 2	2 4	1 8	1 4	2 7	2 0	1 6	1 2	8
			0 . 6	0 . 8	4 9	3 8	3 0	2 5	4 5	3 5	2 8	2 3	3 8	3 0	2 4	2 0	3 2	2 5	2 1	1 7	1 2			
			0 . 5 6	1 . 0	5 4	4 3	3 6	3 0	5 0	4 0	3 3	2 8	4 2	3 5	2 9	2 4	3 5	2 9	2 5	2 1	1 4			
			1 . 2 5	5 9	4 9	4 2	3 6	5 5	4 6	3 9	3 4	4 6	3 9	3 4	2 9	3 9	3 3	2 9	2 5	1 8				
下方投影面積		c m ²	1 . 5	6 3	5 3	4 6	4 0	5 8	5 0	4 3	3 8	4 9	4 3	3 7	3 3	4 1	3 6	3 2	2 8	2 0				
			2 . 0	6 8	6 0	5 3	4 7	6 3	5 6	5 0	4 5	5 4	4 8	4 3	3 9	4 5	4 0	3 7	3 3	2 4				
等価発光面積		c m ²	2 . 5	7 1	6 4	5 8	5 3	6 6	6 0	5 4	4 9	5 7	5 1	4 7	4 3	4 8	4 4	4 0	3 7	2 7				
			3 . 0	7 4	6 7	6 1	5 7	6 9	6 3	5 8	5 3	5 9	5 4	5 0	4 6	5 0	4 6	4 3	4 0	2 9				
H m	1 . 5 4 H m	1 . 5 5 H m	4 . 0	7 7	7 1	6 7	6 2	7 2	6 7	6 2	5 8	6 2	5 8	5 4	5 1	5 2	4 9	4 7	4 4	3 3				
			5 . 0	7 9	7 4	7 0	6 6	7 4	6 9	6 6	6 2	6 4	6 0	5 7	5 4	5 4	5 2	4 9	4 7	3 5				
			7 . 0	8 1	7 8	7 4	7 1	7 6	7 3	7 0	6 7	6 6	6 3	6 1	5 9	5 7	5 4	5 2	5 1	3 9				
			1 0 . 0	8 3	8 1	7 8	7 5	7 8	7 6	7 3	7 1	6 8	6 6	6 4	6 2	5 8	5 7	5 5	5 4	4 1				

