

# 屋内照明器具特性

|         |                    |           |
|---------|--------------------|-----------|
| 品番 (品名) | LSEB1182           |           |
| 光源      | LED6200_70_6099 x1 | 6099.0 lm |
| 管理番号    | K0168476(0)DB1     |           |
| BZ分類    | BZ5                |           |

|        |                  |          |                  |     |     |    |     |     |    |    |     |     |    |    |     |     |    |    |    |    |     |
|--------|------------------|----------|------------------|-----|-----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|----|----|-----|
| 器具効率   | 100%             | 天井       | 80%              |     |     |    | 70% |     |    |    | 50% |     |    |    | 30% |     |    |    | 0% |    |     |
|        | 上方光束<br>7%       |          | 反射率              | 70  | 50  | 30 | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10 | 0% |     |
| 下方光束   | 93%              | 床        |                  | 10% |     |    |     | 10% |    |    |     | 10% |    |    |     | 10% |    |    |    | 0% |     |
| 室指数    | 照明率 ( X0.01 )    |          |                  |     |     |    |     |     |    |    |     |     |    |    |     |     |    |    |    |    | ZCM |
| 保守率    | 良                | 0.63     | 0.6              | 54  | 42  | 34 | 28  | 53  | 41 | 33 | 28  | 49  | 39 | 32 | 27  | 47  | 38 | 32 | 27 | 25 |     |
|        | 中                | 0.6      | 0.8              | 64  | 52  | 44 | 38  | 62  | 51 | 44 | 38  | 59  | 49 | 42 | 37  | 55  | 47 | 41 | 36 | 34 |     |
|        | 否                | 0.56     | 1.0              | 71  | 60  | 52 | 46  | 69  | 58 | 51 | 45  | 65  | 56 | 49 | 44  | 61  | 54 | 48 | 43 | 40 |     |
|        |                  |          | 1.25             | 77  | 67  | 59 | 53  | 75  | 65 | 58 | 53  | 70  | 63 | 56 | 51  | 67  | 60 | 55 | 50 | 47 |     |
| 下方投影面積 | c m <sup>2</sup> |          | 1.5              | 81  | 72  | 65 | 59  | 79  | 70 | 63 | 58  | 74  | 67 | 61 | 57  | 71  | 65 | 60 | 55 | 52 |     |
|        | 等価発光面積           |          | c m <sup>2</sup> | 2.0 | 87  | 79 | 73  | 67  | 84 | 77 | 71  | 66  | 80 | 74 | 69  | 65  | 76 | 71 | 67 | 63 | 59  |
| 取付高さ   | 器具間隔最大限          |          | 2.5              | 90  | 84  | 78 | 73  | 88  | 82 | 77 | 72  | 84  | 79 | 74 | 70  | 80  | 75 | 72 | 68 | 64 |     |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0              | 93  | 87  | 82 | 77  | 91  | 85 | 80 | 76  | 86  | 82 | 78 | 74  | 82  | 79 | 75 | 72 | 68 |     |
| H m    | 1.34 H m         | 1.34 H m | 4.0              | 96  | 91  | 87 | 83  | 94  | 90 | 86 | 82  | 90  | 86 | 83 | 80  | 86  | 83 | 80 | 77 | 73 |     |
|        |                  |          | 5.0              | 98  | 94  | 91 | 87  | 96  | 92 | 89 | 86  | 92  | 89 | 86 | 83  | 88  | 85 | 83 | 81 | 76 |     |
|        |                  |          | 7.0              | 100 | 97  | 95 | 92  | 98  | 96 | 93 | 91  | 94  | 92 | 90 | 88  | 90  | 88 | 87 | 85 | 80 |     |
|        |                  |          | 10.0             | 102 | 100 | 98 | 96  | 100 | 98 | 96 | 94  | 96  | 94 | 93 | 91  | 92  | 91 | 90 | 88 | 84 |     |

