

# 屋内照明器具特性

|         |                   |           |
|---------|-------------------|-----------|
| 品番 (品名) | LGD3403           |           |
| 光源      | LED2700_70_505 x1 | 505.0 l m |
| 管理番号    | K0154665 (0) DB 1 |           |
| BZ分類    | BZ4/0.7/BZ3       |           |

|        |                  |          |                  |      |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |    |     |
|--------|------------------|----------|------------------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|-----|
| 器具効率   | 100%             | 天井       | 80%              |      |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |    |    | 0% |    |     |
|        | 上方光束<br>0%       |          | 反射率              | 70   | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10 | 0% |     |
| 下方光束   | 100%             | 床        |                  | 10%  |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |    |    |    | 0% |     |
| 室指数    | 照明率 ( X0.01 )    |          |                  |      |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |    | ZCM |
| 保守率    | 良                | 0.67     | 0.6              | 61   | 50  | 42  | 37  | 60  | 49  | 42  | 37  | 58  | 48  | 42  | 37  | 56  | 47 | 41 | 37 | 35 |     |
|        | 中                | 0.63     | 0.8              | 71   | 61  | 54  | 49  | 70  | 61  | 54  | 49  | 68  | 59  | 53  | 49  | 65  | 58 | 53 | 48 | 47 |     |
|        | 否                | 0.56     | 1.0              | 78   | 69  | 62  | 57  | 77  | 68  | 62  | 57  | 74  | 67  | 61  | 57  | 72  | 65 | 60 | 56 | 54 |     |
|        |                  |          | 1.25             | 84   | 76  | 70  | 65  | 83  | 75  | 69  | 65  | 80  | 74  | 68  | 64  | 78  | 72 | 68 | 64 | 62 |     |
| 下方投影面積 | c m <sup>2</sup> |          | 1.5              | 88   | 81  | 75  | 71  | 87  | 80  | 75  | 70  | 84  | 78  | 74  | 70  | 81  | 77 | 73 | 69 | 67 |     |
|        | 等価発光面積           |          | c m <sup>2</sup> | 2.0  | 93  | 87  | 83  | 79  | 92  | 86  | 82  | 78  | 89  | 85  | 81  | 77  | 87 | 83 | 79 | 77 | 74  |
| 取付高さ   | 器具間隔最大限          |          | 2.5              | 96   | 91  | 87  | 84  | 95  | 90  | 87  | 83  | 92  | 88  | 85  | 82  | 90  | 87 | 84 | 81 | 79 |     |
|        | H m              | 1.23 H m | 縦方向 ( B )        | 3.0  | 98  | 94  | 91  | 87  | 97  | 93  | 90  | 87  | 94  | 91  | 88  | 86  | 92 | 89 | 87 | 85 | 82  |
|        |                  |          | 横方向 ( A )        | 4.0  | 101 | 98  | 95  | 92  | 100 | 97  | 94  | 91  | 97  | 95  | 92  | 90  | 95 | 93 | 91 | 89 | 86  |
|        |                  |          |                  | 5.0  | 102 | 100 | 97  | 95  | 101 | 99  | 96  | 94  | 99  | 97  | 95  | 93  | 96 | 95 | 93 | 91 | 89  |
|        |                  |          |                  | 7.0  | 104 | 102 | 100 | 99  | 103 | 101 | 99  | 98  | 100 | 99  | 97  | 96  | 98 | 97 | 96 | 95 | 92  |
|        |                  |          |                  | 10.0 | 105 | 104 | 103 | 101 | 104 | 103 | 102 | 100 | 102 | 101 | 100 | 99  | 99 | 99 | 98 | 97 | 94  |

