

屋内照明器具特性	
品番 (品名)	L G B 8 1 6 8 3 F
光源	LDA5 L - D - G - E17 / S / Z4 ×1 440.0 l m
管理番号	K0175929 (0) DR 1
B Z 分類	BZ7 / 0.7 / BZ6 / 3.5 / BZ7 / 4.5 / BZ6 / 6.0 / BZ7

器具効率		58 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		30 %	室指数	照明率 (X0.01)																	Z	C	M
下方光束		28 %																					
保守率		良 中 否	0.63	0.6	27	20	16	13	25	19	15	12	20	16	12	10	16	13	10	8	5		
			0.6	0.8	32	25	21	17	29	23	19	16	24	20	16	14	19	16	13	11	8		
			0.56	1.0	35	29	24	21	32	27	23	20	27	22	19	17	22	18	16	14	9		
				1.25	39	33	28	25	35	30	26	23	29	25	22	20	24	21	18	16	11		
下方投影面積		c m ²		1.5	41	35	31	28	37	33	29	26	31	27	24	22	25	22	20	18	12		
等価発光面積			c m ²		2.0	44	39	35	32	40	36	33	30	33	30	28	25	27	25	23	21	14	
取付 高さ	器具間隔最大限				2.5	46	42	38	35	42	39	35	33	35	32	30	28	29	27	25	23	16	
	横方向 (A)			縦方向 (B)			3.0	47	44	40	38	44	40	38	35	36	34	32	30	30	28	26	25
H m	1.33 H m	1.30 H m			4.0	49	46	44	41	45	43	40	38	38	36	34	33	31	30	28	27	19	
				5.0	50	48	46	43	47	44	42	40	39	37	36	34	32	31	30	29	20		
				7.0	52	50	48	46	48	46	45	43	40	39	38	37	33	32	31	30	21		
				10.0	53	51	50	49	49	48	46	45	42	40	40	39	34	34	33	32	23		

