

| 屋内照明器具特性 |                                            |
|----------|--------------------------------------------|
| 品番 (品名)  | L G W8 5 0 8 0 F                           |
| 光源       | LDA5 L - D - G - E17 / S / Z4 ×1 440.0 l m |
| 管理番号     | K0175937 ( 0 ) DR 1                        |
| B Z 分類   | BZ8 / 0.9 / BZ7                            |

| 器具効率     |           | 81 %             | 反射率              | 天井            | 80 % |    |    |    |    | 70 % |    |    |    |    | 50 % |    |    |    |    | 30 % |     |    |  |       | 0 % |
|----------|-----------|------------------|------------------|---------------|------|----|----|----|----|------|----|----|----|----|------|----|----|----|----|------|-----|----|--|-------|-----|
|          |           |                  |                  | 壁             | 70   | 50 | 30 | 10 | 70 | 50   | 30 | 10 | 70 | 50 | 30   | 10 | 70 | 50 | 30 | 10   | 0 % |    |  |       |     |
|          |           |                  |                  | 床             | 10 % |    |    |    |    | 10 % |    |    |    |    | 10 % |    |    |    |    | 10 % |     |    |  |       | 0 % |
| 上方光束     |           | 39 %             | 室指数              | 照明率 ( X0.01 ) |      |    |    |    |    |      |    |    |    |    |      |    |    |    |    |      |     |    |  | Z C M |     |
| 下方光束     |           | 42 %             |                  |               |      |    |    |    |    |      |    |    |    |    |      |    |    |    |    |      |     |    |  |       |     |
| 保守率      |           | 良<br>中<br>否      | 0.63             | 0.6           | 37   | 27 | 20 | 16 | 34 | 25   | 19 | 15 | 28 | 21 | 16   | 13 | 23 | 17 | 13 | 10   | 6   |    |  |       |     |
|          |           |                  | 0.6              | 0.8           | 44   | 34 | 27 | 22 | 40 | 31   | 25 | 21 | 33 | 26 | 22   | 18 | 27 | 22 | 18 | 15   | 10  |    |  |       |     |
|          |           |                  | 0.56             | 1.0           | 49   | 39 | 32 | 27 | 45 | 36   | 30 | 26 | 37 | 31 | 26   | 22 | 30 | 25 | 21 | 18   | 12  |    |  |       |     |
|          |           |                  |                  | 1.25          | 53   | 44 | 38 | 33 | 49 | 41   | 35 | 30 | 41 | 35 | 30   | 26 | 33 | 29 | 25 | 22   | 15  |    |  |       |     |
| 下方投影面積   |           | c m <sup>2</sup> | 1.5              | 56            | 48   | 42 | 37 | 52 | 45 | 39   | 34 | 43 | 38 | 33 | 29   | 36 | 31 | 28 | 25 | 17   |     |    |  |       |     |
| 等価発光面積   |           |                  | c m <sup>2</sup> | 2.0           | 61   | 54 | 48 | 43 | 56 | 50   | 45 | 40 | 47 | 42 | 38   | 35 | 39 | 35 | 32 | 29   | 20  |    |  |       |     |
| 取付<br>高さ | 器具間隔最大限   |                  | 2.5              | 64            | 58   | 52 | 48 | 59 | 54 | 49   | 45 | 50 | 45 | 42 | 38   | 41 | 38 | 35 | 32 | 23   |     |    |  |       |     |
|          | 横方向 ( A ) |                  | 縦方向 ( B )        |               | 3.0  | 66 | 61 | 56 | 51 | 61   | 56 | 52 | 48 | 52 | 48   | 44 | 41 | 43 | 40 | 37   | 35  | 25 |  |       |     |
| H m      | 1.59 H m  | 1.73 H m         | 4.0              | 69            | 64   | 60 | 56 | 64 | 60 | 56   | 53 | 54 | 51 | 48 | 45   | 45 | 43 | 40 | 38 | 27   |     |    |  |       |     |
|          |           |                  | 5.0              | 71            | 67   | 63 | 60 | 66 | 62 | 59   | 56 | 56 | 53 | 51 | 48   | 47 | 45 | 43 | 41 | 29   |     |    |  |       |     |
|          |           |                  | 7.0              | 73            | 70   | 67 | 64 | 68 | 65 | 62   | 60 | 58 | 56 | 54 | 52   | 49 | 47 | 45 | 44 | 32   |     |    |  |       |     |
|          |           |                  | 10.0             | 75            | 72   | 70 | 68 | 69 | 67 | 65   | 63 | 60 | 58 | 56 | 55   | 50 | 49 | 48 | 47 | 34   |     |    |  |       |     |

