

屋内照明器具特性	
品番 (品名)	L G W8 5 0 9 0 F
光源	LDA5 L - D - G - E17 / S / Z4 ×1 440.0 l m
管理番号	K0130458 (0) DB1
BZ分類	BZ9 / 2.8 / BZ8

器具効率		71 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		35 %	室指数	照明率 (X0.01)																		Z C M
下方光束		36 %																				
保守率		良 中 否	0.63	0.6	32	23	17	13	29	21	16	12	24	17	13	10	19	14	10	8	4	
			0.6	0.8	38	29	23	18	34	26	21	17	28	22	17	14	23	18	14	11	7	
			0.56	1.0	42	33	27	22	38	31	25	21	31	25	21	18	25	21	17	14	9	
				1.25	46	38	32	27	42	35	29	25	34	29	25	21	28	23	20	17	11	
下方投影面積		c m ²	1.5	49	41	35	31	44	38	33	28	37	32	27	24	30	26	22	20	13		
等価発光面積			c m ²	2.0	53	46	41	36	48	43	38	34	40	36	32	29	33	29	26	24	16	
取付 高さ	器具間隔最大限		2.5	55	49	45	40	51	46	41	38	42	38	35	32	35	32	29	26	18		
	横方向 (A)		縦方向 (B)	3.0	57	52	48	44	53	48	44	41	44	41	37	35	36	33	31	29	19	
H m	1.62 H m	1.98 H m	4.0	60	55	52	48	55	51	48	45	46	43	41	38	38	36	34	32	22		
			5.0	61	58	54	51	57	53	50	48	48	45	43	41	40	38	36	34	24		
			7.0	63	60	58	55	59	56	54	51	50	48	46	44	41	40	38	37	26		
			10.0	65	63	61	59	60	58	56	55	51	50	48	47	43	42	41	39	28		

