

屋内照明器具特性	
品番 (品名)	L G W8 0 3 2 2 K
光源	LED5000_70_215 ×1 215.0 l m
管理番号	K0146942 (0) DB 1
B Z 分類	BZ6 / 0.7 / BZ5 / 3.5 / BZ6

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	5 1	3 9	3 2	2 6	4 9	3 8	3 1	2 5	4 4	3 4	2 8	2 4	3 9	3 1	2 6	2 2	1 8
			0 . 6	0 . 8	6 1	4 9	4 1	3 6	5 7	4 7	4 0	3 4	5 1	4 3	3 7	3 2	4 6	3 9	3 4	3 0	2 5
			0 . 5 6	1 . 0	6 7	5 6	4 8	4 2	6 3	5 4	4 6	4 1	5 7	4 9	4 3	3 8	5 1	4 4	3 9	3 5	3 0
				1 . 2 5	7 3	6 3	5 5	4 9	6 9	6 0	5 3	4 8	6 2	5 5	4 9	4 4	5 5	5 0	4 5	4 1	3 5
下方投影面積		c m ²		1 . 5	7 7	6 7	6 0	5 5	7 3	6 4	5 8	5 3	6 5	5 9	5 3	4 9	5 9	5 3	4 9	4 5	3 9
			等価発光面積	c m ²	2 . 0	8 2	7 4	6 8	6 2	7 8	7 1	6 5	6 0	7 0	6 5	6 0	5 6	6 3	5 9	5 5	5 1
取付 高さ	器具間隔最大限			2 . 5	8 5	7 9	7 3	6 8	8 1	7 5	7 0	6 5	7 3	6 8	6 4	6 0	6 6	6 2	5 9	5 6	4 8
	横方向 (A) 縦方向 (B)			3 . 0	8 8	8 2	7 6	7 2	8 4	7 8	7 3	6 9	7 6	7 1	6 7	6 4	6 8	6 5	6 2	5 9	5 0
H m	1 . 3 0 H m	1 . 3 1 H m		4 . 0	9 1	8 6	8 1	7 8	8 7	8 2	7 8	7 5	7 9	7 5	7 2	6 9	7 1	6 8	6 6	6 3	5 4
				5 . 0	9 3	8 9	8 5	8 1	8 9	8 5	8 1	7 8	8 0	7 7	7 5	7 2	7 3	7 0	6 8	6 6	5 7
				7 . 0	9 5	9 2	8 9	8 6	9 1	8 8	8 5	8 3	8 3	8 0	7 8	7 6	7 5	7 3	7 1	7 0	6 0
				1 0 . 0	9 7	9 5	9 2	9 0	9 3	9 1	8 8	8 6	8 5	8 3	8 1	8 0	7 7	7 5	7 4	7 3	6 3

