

屋内照明器具特性	
品番 (品名)	L G W C 8 0 3 2 0 K
光源	LED5000_70_317 x1 317.0 lm
管理番号	K0149618 (0) DR 1
B Z 分類	BZ10 / 0.9 / BZ9

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		50 %	室指数	照明率 (X0.01)																			Z C M			
下方光束		50 %																								
保守率		良 中 否	0.63	0.6	43	31	22	17	39	28	21	15	32	23	17	13	25	18	13	10	4					
			0.6	0.8	52	39	30	24	47	36	28	22	38	29	23	18	30	23	18	14	8					
			0.56	1.0	58	45	37	30	52	41	34	28	43	34	28	23	34	27	22	18	10					
				1.25	63	52	43	36	57	47	39	33	47	39	33	28	37	31	26	22	13					
下方投影面積		c m ²	1.5	67	56	48	41	61	52	44	38	50	43	37	32	40	34	30	26	16						
等価発光面積			c m ²	2.0	73	63	56	49	67	58	51	46	55	48	43	38	44	39	35	31	20					
取付 高さ	器具間隔最大限		2.5	77	68	61	55	70	63	56	51	58	52	47	43	47	43	39	35	23						
	横方向 (A)		縦方向 (B)		3.0	79	72	65	60	73	66	60	55	61	55	51	47	49	45	42	38	25				
H m	0.00 H m		1.54 H m		4.0	83	77	71	66	76	71	66	61	64	60	56	52	52	49	46	43	29				
					5.0	85	80	75	70	79	74	69	65	66	62	59	56	54	51	49	46	31				
					7.0	88	84	80	76	82	78	74	71	69	66	63	60	57	55	52	50	35				
					10.0	90	87	84	81	84	81	78	75	71	69	67	64	59	57	56	54	38				

