

<b>屋内照明器具特性</b>	
品番 (品名)	<b>L S L G 9 0 8</b>
光源	LLD4000LSCB1 ×1      845.0 lm
管理番号	K0176416 ( 0 ) DR 1
B Z 分類	BZ5 / 0.7 / BZ4

器具効率	38%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	19%	室指数	床	10%				10%				10%				10%				0%
下方光束	19%		照明率 ( X0.01 )	Z C M																
保守率	良 0.63 中 0.6 否 0.56		0.6	19	15	12	10	18	14	12	10	15	12	10	9	13	10	9	8	6
			0.8	23	19	16	14	21	18	15	13	18	15	13	12	15	13	12	10	8
			1.0	25	22	19	17	23	20	18	16	20	17	16	14	17	15	14	12	9
			1.25	27	24	22	20	25	23	20	19	22	19	18	16	18	17	15	14	11
下方投影面積	c m <sup>2</sup>	1.5	29	26	24	22	27	24	22	20	23	21	19	18	19	18	17	16	12	
等価発光面積		2.0	31	28	26	25	29	26	25	23	24	23	22	20	21	19	18	18	13	
取付高さ		器具間隔最大限		2.5	32	30	28	27	30	28	26	25	25	24	23	22	21	21	20	14
		横方向 (A)	縦方向 (B)	3.0	33	31	29	28	31	29	28	26	26	25	24	23	22	21	21	15
		H <sub>m</sub>	0.00H <sub>m</sub>	1.64H <sub>m</sub>	4.0	34	33	31	30	32	30	29	28	27	26	25	25	23	22	16
			5.0	35	33	32	31	32	31	30	29	28	27	26	26	23	23	22	16	
			7.0	35	34	34	33	33	32	31	31	28	28	27	27	24	24	23	17	
			10.0	36	35	35	34	33	33	32	32	29	28	28	28	24	24	24	18	

