

# 屋内照明器具特性

品番 (品名)	L S E W 2 0 2 4				
光源	LLD6300N ×1                      1270.0 l m				
管理番号	K0165621 ( 0 ) DB 1				
B Z 分類	B Z 5				

器具効率	76 %	天井	80 %				70 %				50 %				30 %				0 %			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
		床	10 %				10 %				10 %				10 %				0 %			
上方光束	3 %																					
下方光束	73 %																					
室指数	照明率 ( X 0 . 0 1 )																			Z C M		
保守率	良 中 否	0.63	0.6	0.56	0.6	42	33	27	23	41	32	26	22	39	31	26	22	37	30	25	22	20
		0.6	0.8	49	41	34	30	48	40	34	30	46	39	33	29	44	37	33	29	27		
		1.0	1.0	54	46	40	35	53	45	39	35	50	44	39	35	48	42	38	34	32		
		0.56	1.25	59	51	45	41	57	50	45	41	55	49	44	40	52	47	43	39	37		
下方投影面積	c m <sup>2</sup>	1.5	62	55	49	45	60	54	49	45	58	52	48	44	55	50	46	43	41			
		2.0	66	60	55	51	65	59	55	51	62	57	53	50	59	55	52	49	46			
取付高さ	器具間隔最大限		2.5	69	64	59	55	67	63	58	55	64	60	57	54	62	58	55	53	50		
	横方向 ( A )	縦方向 ( B )	3.0	71	66	62	59	69	65	61	58	66	63	60	57	64	61	58	56	53		
H m	1.25 H m	1.25 H m	4.0	73	69	66	63	72	68	65	62	69	66	63	61	66	64	62	60	57		
			5.0	75	72	69	66	73	70	68	65	71	68	66	64	68	66	64	62	60		
			7.0	77	74	72	70	75	73	71	69	72	71	69	67	70	68	67	66	63		
			10.0	78	76	74	73	77	75	73	72	74	73	71	70	72	70	69	68	65		

