

屋内照明器具特性	
品番 (品名)	L G W C 8 0 3 3 0 K
光源	LED5000_70_267 x1 267.0 l m
管理番号	K0149622 (0) DR 1
B Z 分類	B Z 9

器具効率		100 % 上方光束 50 % 下方光束	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.63	0.6	44	31	23	17	40	29	21	16	33	24	18	13	26	19	14	10	5
			0.6	0.8	52	39	31	25	47	36	28	23	39	30	24	19	31	24	19	15	8
			0.56	1.0	58	46	37	30	53	42	34	28	43	35	28	23	34	28	23	19	11
				1.25	63	52	43	37	58	48	40	34	47	39	33	28	38	32	27	23	14
下方投影面積 等価発光面積		cm ² cm ²	1.5	67	57	48	42	61	52	45	39	50	43	37	32	40	35	30	26	16	
			2.0	73	64	56	50	67	58	52	46	55	49	43	39	44	39	35	31	20	
			2.5	77	68	61	55	70	63	57	51	58	53	48	43	47	43	39	35	23	
取付 高さ	器具間隔最大限		3.0	79	72	65	60	73	66	60	55	61	55	51	47	49	45	42	38	25	
	横方向 (A)	縦方向 (B)	4.0	83	77	71	66	76	71	66	61	64	60	56	52	52	49	46	43	29	
H m	1.38 H m	1.30 H m	5.0	85	80	75	70	79	74	69	65	66	62	59	56	54	51	49	46	31	
			7.0	88	84	80	76	82	78	74	71	69	66	63	60	57	54	52	50	35	
			10.0	90	87	84	81	84	81	78	75	71	69	67	64	59	57	55	54	38	

